



Best choice.

Bystronic Tools

Laser | Bending | Waterjet
bystronic.com

Overview about the icons used in this catalogue



Material / Hardness



max. permitted load



method of tool loading



nature of load



max. box depth



weight



availability / delivery time



clamping type



drawing number (BOSbase reference)



reversible tool



bottom tool support

Content

The Bystronic "bending world" 4

Air bending (Xpert / Xact)

basis of calculation 14

upper tools and bottom tools Xpert 20

upper tools and bottom tools Xact 110

3-point-bending (Hämmerle 3P)

basis of calculation 160

upper tools and bottom tools 168

Workshop

Taking bending into design

Small bending radii?
Short flange length?
Too much welding, cleaning and flattening?
Bending marks?



What are the topics?

- Basics
- Software presentations
- Machine presentations
- Industrial design expert talks
- Case studies
- Your questions

You can obtain date and further information from our consulting engineers,
all contact dates you can be found on the last page.

Further information can be obtained at: www.bystronic.com

Bending seminar

Bending of high tensile strength materials

Material costs are too high?
Wear and tear resistance relevant?
Challenge light construction?
Steel broken yet?




What are the topics?

- Basics
- Experts talks of steel producers
- How the software can help
- Bend case studies
- Specialist talks

You can obtain date and further information from our consulting engineers,
all contact data can be found on the last page.


Further information can be obtained at: www.bystronic.com



Special tools are also part of the Bystronic tooling range.

Our tooling specialist will help you to solve your forming problems,
all contact information are located at the end of the catalog.


Visit our shop in the Internet under: www.bystronic.com



Bystronic bending methods


Air bending

For material thicknesses up to 50 mm mild steel



Coining


For material thicknesses up to 3 mm mild steel



Bystronic bending methods

3-point-bending


Up to 12 mm mild steel



Bystronic bending methods

Principle of air bending


With the air bending method the bending angle is determined by the depth of penetration of the upper tool into the lower die. To that effect and amongst other factors the bending accuracy is mainly dependant upon the positional accuracy of the upper beam. Under load the material is stressed from A to C. After removal of the load the portions AD and EC spring back into their original positions. In the case of air bending without bottoming the vees of the bottom tool and the angle of the top tool must be smaller than 90°.




- | | | |
|---|---|---------------------|
| M | = | bottom tool |
| R | = | inner radius |
| V | = | bottom tool opening |
| S | = | upper tool |

Bystronic bending methods

Principle of bottoming



As soon as the areas AD and CE touch the sides of the vee in air bending with bottoming they will spring back into their original position until the positions of contact have to move to D and E.




A still further penetration of the top tool will result in a disengagement of the points D and E from the lower die as the points of contact start to move in the overbending is larger than the spring back of the portion located underneath the points of contact the angle of the section after removal of the load will be smaller than the angle of the vee..

Bystronic bending methods

Principle of coining

A further penetration of the top tool will result in a reopening of the section D and E until the top tool completely bottoms out on to the material. (start of the coining process).

The variation of the forces versus the travel of the top tool is a function of the material. The bottoming or coining process corresponds to a continuous reduction of the die opening (V). The smaller the width of the vee during coining results in a corresponding reduction of spring back in comparison to airbending. The bending forces required are 4 to 8 times greater than those required for air bending.




Bystronic bending methods

Principle of 3-point-bending

For the 3-point-bending the bottom tool groove depth (H) is accomplished with an accuracy of 1/1000 mm by means of a precise wedge system. With given sheet metal quality, sheet metal characteristics and plate thickness and taking resilience of the part into account, the bend angle to be produced is governed predictably and accurately by bottom tool depth (F). The top tool segments positioned along the bending line thereby adapts to the bending line of the bottom tools. The hydraulic cushion compensates for machine and material related factors.

The 3-point-bending process is something in between air bending and coining and delivers highest accuracy and flexibility. It opens new possibilities in designing and manufacturing of parts.



M	=	lower die
P	=	vee pin
H	=	vee depth
V	=	vee width
K	=	hydraulic cushion
S	=	upper tool

Calculation basics for air bending


Capacity chart for air bending

The given data has been calculated based upon bending material with a tensile strength of $R_m = 420 \text{ N/mm}^2$ over a length of 1 m.

Sheets with mill scale will increase the bending force by a factor of 1,05–1,1

Calculation basics for air bending

Capacity chart for air bending



The internal radius R corresponds to approximately 16% of the die opening V.

Calculation basics for air bending

Calculation formulas

Recommended bottom tool opening V for air bending

Material thickness	t	0.5–2.5 mm	3–8 mm	9–10 mm	> 12 mm
Bottom tool opening	V	6 × t	8 × t	10 × t	12 × t

Bending force for

Aluminium	$R_m = 300 \text{ N/mm}^2$	$F = F(\text{table}) \times 0.65$
Mild steel	$R_m = 420 \text{ N/mm}^2$	$F = F(\text{table})$
Stainless steel	$R_m = 700 \text{ N/mm}^2$	$F = F(\text{table}) \times 1.6$

Determination of the bending force for air bending (reference data)

$$F = \frac{Rm \times t^2}{V} \times \left(1 + \frac{4 \times t}{V}\right)$$

Conversion: $R_m = \text{tensile strength in N/mm}^2$

$$10 \text{ N} \approx 1 \text{ kg}$$

$10 \text{ kN} \approx 1 \text{ t}$

Conversion for minimal interpal radii R

thickness t	1	2	3	4	5	6	8	10	12	16	18	20
min. R	1	2	3	5	6	8	12	16	20	28	36	40

Calculation basics for air bending

Tensile strength

Steel	Tensile strength
GG-20	Rm = 200 N/mm ²
GGG-40	Rm = 400 N/mm ²
G-X 6 CrNi 18 9	Rm = 450 N/mm ²
S 355 MC	Rm = 550 N/mm ²
S 420 MC	Rm = 550 N/mm ²
S 460 MC	Rm = 620 N/mm ²
GS-60	Rm = 650 N/mm ²
S 500 MC	Rm = 700 N/mm ²
S 550 MC	Rm = 760 N/mm ²
S 600 MC	Rm = 820 N/mm ²
S 650 MC	Rm = 880 N/mm ²
S 700 MC	Rm = 950 N/mm ²
42 CrMo 4	Rm = 1000 N/mm ²

Please ask your
responsible
Consultant
for bending high
strength materials.

Notes

Calculation basis for air bending

18

Working space determination

Tonnage	Day-light	Day-light	Stroke	Punch height	Working height	Clamping height	Box depth	Die height	Table height	Free space	Width upper beam
	DL mm	DLW mm	SH mm	PH mm	WH mm	CH mm	BH mm	DH mm	TH mm	FS mm	UB mm
			Modufix			**				*	
			Wila			**					
60t	500	420	215	155	116	39	53.2	55	145	184	80
				175	115	60	52.5	55	145	185	80
				250	190	60	105	55	145	110	80
100t	500	420	215	155	116	39	56.7	55	145	184	70
				175	115	60	56	55	145	185	70
				250	190	60	108.5	55	145	110	70
150t	500	420	215	155	116	39	56.7	55	145	184	70
				175	115	60	56	55	145	185	70
				250	190	60	108.5	55	145	110	70
200t	500	420	215	155	116	39	53.2	55	145	184	80
				175	115	60	52.5	55	145	185	80
				250	190	60	105	55	145	110	80
250t	550	470	265	155	116	39	53.2	55	145	234	80
				175	115	60	52.5	55	145	235	80
				250	190	60	105	55	145	160	80
320t	550	470	265	155	116	39	46.2	55	145	234	100
				175	115	60	54.5	55	145	235	100
				250	190	60	98	55	145	160	100

* Not valid for WILA Modufix,

** Clamping height S/R/Wila = 39, RF/RF-A = 60

Calculation formula



for box depth. $BH = (PH - CH - UB : 2) \times 0,7$

To calculate the remaining working day light for given machine and tool combination. $FS = DL - TH - DH - WH$

Calculation basics for air bending

Working space determination

19



Air bending

Upper tools Xpert



Upper tools Xpert


Recommendation starterkit Xpert 60 - 320

Bend length	Part number	Designation	Pieces	Unit
2050 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	4	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	2	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
2550 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	5	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	2	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
3100 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	6	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	3	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
4100 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	8	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	4	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece



Description upper tools

Clamping R

R mechanical
(Standard Xpert 60 – 320)




R hydraulic
(Optional Xpert 60 - 320)





Description upper tools

Clamping RF

RF mechanical
(Standard Xpert 250 – 1000)



RF hydraulic
(Optional Xpert 250 - 1000)



Head support $\leq 1600 \text{ kN/m}$ shoulder supp. $> 1600 \text{ kN/m}$



Sideways and vertical insertion possible



Head and shoulder supported possible



Mechanical and hydraulic



Tools are reversible

Because of the height of the clamping area, R type is suitable for light - medium duty clamping applications.



Head support $\leq 1600 \text{ kN/m}$ shoulder supp. $> 1600 \text{ kN/m}$



Sideways and vertical insertion possible



Head and shoulder supported possible



Mechanical and hydraulic



Because of the height the RF type clamping is suitable for medium to high applications.


Description upper tools

24

Clamping RF-A

RF-A hydraulic

(Optional Xpert 60 - 320 and Xpert 250 - 1000)



The automatic centering of the RF-A hydraulic clamping system helps to shorten the setup time by up to 20%. This combined with the large clamping area makes it a very popular option among users of both Xpert 60-320 machines and also the large Xpert machines 250 - 1000.

Head support $\leq 1600 \text{ kN/m}$ shoulder supp. $> 1600 \text{ kN/m}$

Sideways and vertical insertion possible

Maximum tool weight
50 kg / m

Head and shoulder supported possible

Hydraulic


Tools are reversible

Description upper tools

25

Clamping MAMMUT Ergo

MAMMUT Ergo hydraulic



Head supported $\leq 3200 \text{ kN/m}$ shoulder su. $> 3200 \text{ kN/m}$

Sideways insertion

Head and shoulder supported possible

Hydraulic


Tools are reversible

The MAMMUT Ergo is specially designed for high loads and the use of heavy tools. The MAMMUT Ergo is designed with casters for easy and quick tooling setup.

Description upper tools

Upper tool segments for R / RF / RF-A

Horns R / RF / RF-A



FSC / 1000 mm

$$(10 + 15 + 20 + 30 + 50 + 100 + 200 + 275 + 300)$$



FSL / 1100 mm)

$$(10 + 15 + 20 + 30 + 50 + 100 + 200 + 375 + 300)$$



Notes

27

P2 RF-A H175

Upper Tools

28



[R] Radius (mm) 1

Nose angle 85°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

$F_{max} = 1300 \text{ kN/m}$

Operator side

Head supported

24.1 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BOS No. BY1C003

Standard length	Part number
515 mm	65206.0002.5001
1030 mm	65206.0002.3004
1000 mm sect. FSC	65206.0002.0003
1100 mm sect. FSL	65206.0002.1001
Horn set LH + RH	65206.0002.7001



P2 RF-A / 85°
F = 1300 kN/m
R = 1 mm
H = 175 mm

Upper Tools

29

P2 RF-A H250

Upper Tools

30




[R] Radius (mm)	1
Nose angle	85°
[H] Height (mm)	250

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 34.4 kg/m
- Hydraulic clamping
- 98.0 mm
- Ex stock / 24 h
- BY1C004

Standard length	Part number
515 mm	65206.0002.5005
1030 mm	65206.0002.3009
1000 mm sect. FSC	65206.0002.0001
1100 mm sect. FSL	65206.0002.1004
Horn set LH + RH	65206.0002.7003

31



P2 RF-A / 85°
 F = 1000 kN/m
 R = 1 mm
 H = 250 mm

Upper Tools

P3 RF-A H175

[R] Radius (mm) 1

Nose angle 85°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

F_{max} = 1300 kN/m

Operator side

Head supported

24.5 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BOS No. IB00545

Standard length	Part number
515 mm	65206.0003.5005
1030 mm	65206.0003.3001
1000 mm sect. FSC	65206.0003.0002
1100 mm sect. FSL	65206.0003.1005
Horn set LH + RH	65206.0003.7006



P3 RF-A / 85°
F = 1300 kN/m
R = 1 mm
H = 175 mm

P3 RF-A H250

Upper Tools

34



[R] Radius (mm) 1

Nose angle 85°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

Fmax = 1400 kN/m

Operator side

Head supported

34.8 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BOS No. BY10176


Standard length	Part number
515 mm	65206.0003.5003
1030 mm	65206.0003.3004
1000 mm sect. FSC	65206.0003.0009
1100 mm sect. FSL	65206.0003.1002
Horn set LH + RH	65206.0003.7002



P3 RF-A / 85°
F = 1400 kN/m
R = 1 mm
H = 250 mm

Upper Tools

35

P4 RF-A H175

[R] Radius (mm) 1.5

Nose angle 85°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

F_{max} = 900 kN/m

Operator side

Head supported

31.8 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BY1C011A

Standard length	Part number
515 mm	65206.0004.5005
1030 mm	65206.0004.3005
1000 mm sect. FSC	65206.0004.0003
1100 mm sect. FSL	65206.0004.1002
Horn set LH + RH	65206.0004.7002



P4 RF-A / 85
F = 900 kN/m
R = 1.5 / 1 mm
H = 175 mm

P4 RF-A H250

Upper Tools

38



[R] Radius (mm) 1.5

Nose angle 85°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

$F_{max} = 600 \text{ kN/m}$

Operator side

Head supported

48.3 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BOS No. BY1C012

Standard length	Part number
515 mm	65206.0004.5007
1030 mm	65206.0004.3009
1000 mm sect. FSC	65206.0004.0004
1100 mm sect. FSL	65206.0004.1003
Horn set LH + RH	65206.0004.7003



P4 RF-A / 85
 $F = 600 \text{ kN/m}$
 $R = 1.5 / 1 \text{ mm}$
 $H = 250 \text{ mm}$

Upper Tools

39

P5 RF-A H175

[R] Radius (mm) 1

Nose angle 30°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

F_{max} = 1000 kN/m

Operator side

Head supported

19 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BY1C019

Standard length	Part number
515 mm	65206.0005.5007
1030 mm	65206.0005.3004
1000 mm sect. FSC	65206.0005.0003
1100 mm sect. FSL	65206.0005.1003
Horn set LH + RH	65206.0005.7002



P5 RF-A / 30°
F = 1000 kN/m
R = 1 mm
H = 175 mm

P5 RF-A H250

Upper Tools

42



[R] Radius (mm) 1

Nose angle 30°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

$F_{max} = 750 \text{ kN/m}$

Operator side

Head supported

26 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BOS No. BY1C020

Standard length	Part number
515 mm	65206.0005.5008
1030 mm	65206.0005.3005
1000 mm sect. FSC	65206.0005.0004
1100 mm sect. FSL	65206.0005.1002
Horn set LH + RH	65206.0005.7001



P5 RF-A / 30°
F = 750 kN/m
R = 1 mm
H = 250 mm


Upper Tools

43

P6 RF-A H175

Upper Tools

44



[R] Radius (mm) 1

Nose angle 30°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

Fmax = 1500 kN/m

Operator side

Head supported

23.3 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BY1C023

Standard length	Part number
515 mm	65206.0006.5001
1030 mm	65206.0006.3003
1000 mm sect. FSC	65206.0006.0001
1100 mm sect. FSL	65206.0006.1001
Horn set LH + RH	65203.0006.7002



P6 RF-A / 30°
F = 1500 kN/m
R = 1 mm
H = 175 mm

Upper Tools

45

P6 RF-A H250

Upper Tools

46



[R] Radius (mm) 1

Nose angle 30°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

$F_{max} = 1400 \text{ kN/m}$

Operator side

Head supported

35 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BOS No. BY1C024

Standard length	Part number
515 mm	65206.0006.5002
1030 mm	65206.0006.3002
1000 mm sect. FSC	65206.0006.0002
1100 mm sect. FSL	65206.0006.1003
Horn set LH + RH	65206.0006.7001



P6 RF-A / 30°
F = 1400 kN/m
R = 1 mm
H = 250 mm


Upper Tools

47

P7 RF-A H175

Upper Tools


48



[R] Radius (mm)	3
Nose angle	30°
[H] Height (mm)	175

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1600 \text{ kN/m}$
- Operator side
- Head supported
- 24.2 kg/m
- Hydraulic clamping
- 45.5 mm
- Ex stock / 24 h
- BY1C027

Standard length	Part number
515 mm	65206.0007.5002
1030 mm	65206.0007.3004
1000 mm sect. FSC	65206.0007.0003
1100 mm sect. FSL	65206.0007.1002
Horn set LH + RH	65206.0007.7001



P7 RF-A / 30°
F = 1600 kN/m
R = 3 mm
H = 175 mm

Upper Tools

49

P7 RF-A H250

Upper Tools

50



[R] Radius (mm) 3

Nose angle 30°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

$F_{max} = 1400 \text{ kN/m}$

Operator side

Head supported

35.9 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BOS No. BY1C028

Standard length	Part number
515 mm	65206.0007.5003
1030 mm	65206.0007.3006
1000 mm sect. FSC	65206.0007.0002
1100 mm sect. FSL	65206.0007.1003
Horn set LH + RH	65206.0007.7002



P7 RF-A / 30°
F = 1400 kN/m
R = 3 mm
H = 250 mm

Upper Tools

51

P8 RF-A H175

Upper Tools

52



[R] Radius (mm) 1

Nose angle 85°

[H] Height (mm) 175

42 CrMo 4

58 - 62 HRC

$F_{max} = 1000 \text{ kN/m}$

Operator side

Head supported

26.5 kg/m


Hydraulic clamping

45.5 mm

Ex stock / 24 h

BY10123

Standard length	Part number
515 mm	65206.0008.5002
1030 mm	65206.0008.3003
1000 mm sect. FSC	65206.0008.0001
1100 mm sect. FSL	65206.0008.1003
Horn set LH + RH	65206.0008.7001



P8 RF-A / 85°
F = 1000 kN/m
R = 1 mm
H = 175 mm

Upper Tools

53

P8 RF-A H250

Upper Tools

54



[R] Radius (mm) 1

Nose angle 85°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

F_{max} = 1000 kN/m

Operator side

Head supported

38.3 kg/m


Hydraulic clamping

98.0 mm

Ex stock / 24 h

BY1C032

Standard length	Part number
515 mm	65206.0008.5013
1030 mm	65206.0008.3004
1000 mm sect. FSC	65206.0008.0004
1100 mm sect. FSL	65206.0008.1004
Horn set LH + RH	65206.0008.7002



P8 RF-A / 85°
F = 1000 kN/m
R = 1 mm
H = 250 mm

Upper Tools

55

P9 RF-A H175

Upper Tools


56



[R] Radius (mm)	4
Nose angle	60°
[H] High (mm)	175

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1600 \text{ kN/m}$
- Operator side
- Head supported
- 33.5 kg/m
- Hydraulic clamping
- 45.5 mm
- Ex stock / 24 h
- BY1C039

Standardlänge	Part number
515 mm	65206.0009.5006
1030 mm	65206.0009.3003
1000 mm sect. FSC	65206.0009.0001
1100 mm sect. FSL	65206.0009.1004
Horn set LH + RH	65206.0009.7001



P9 RF-A / 60°
 $F = 1600 \text{ kN/m}$
 $R = 4 \text{ mm}$
 $H = 175 \text{ mm}$

Upper Tools

57

P9 RF-A H250

Upper Tools

58



[R] Radius (mm) 4

Nose angle 60°

[H] Height (mm) 250

42 CrMo 4

58 - 62 HRC

$F_{max} = 1600 \text{ kN/m}$

Operator side

Head supported

51 kg/m


Hydraulic clamping

98.0 mm

Ex Stock / 24 h

BOS No. BY1C040

Standard length	Part number
515 mm	65206.0009.5005
1030 mm	65206.0009.3004
1000 mm sect. FSC	65206.0009.0002
1100 mm sect. FSL	65206.0009.1003
Horn set LH + RH	65206.0009.7002



P9 RF-A / 60°
F = 1600 kN/m
R = 4 mm
H = 250 mm

Upper Tools

59

P10 RF-A H150

Upper Tools


60



[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	150

Standard length	Part number
515 mm	65206.0010.5004
1030 mm	65206.0010.3004

- C45
-
- Fmax = 1600 kN/m
- Operator side
- Head supported
- 34 kg/m
- Hydraulic clamping
-
- Ex stock / 24 h
- BY1C043A**



P10 RF-A
F = 1600 kN/m
H = 150 mm

Upper Tools

61

P10 RF-A H250

Upper Tools

62



[R] Radius (mm) -

Nose angle -

[H] Height (mm) 250



C45



 $F_{max} = 1600 \text{ kN/m}$ 

Operator side



Head supported



66 kg/m



Hydraulic clamping






Ex stock / 24 h



BY50026

Standard length	Part number
515 mm	65206.0010.5005
1030 mm	65206.0010.3003



P10 RF-A
 $F = 1600 \text{ kN/m}$
 $H = 250 \text{ mm}$

Upper Tools

63


P10 RF-A

Round bars suitable for radius bar holder

Hardened radius bars

L	515/1030	515/1030	515/1030	515/1030	515/1030	515/1030
Type	PB 28	PB 30	PB 35	PB 40	PB 45	PB 50
Ø mm	28	30	35	40	45	50
G	5	5.5	7.5	10	12.5	15.5

515/1030	515/1030	515/1030	515/1030	515/1030
PB 55	PB 60	PB 65	PB 70	PB 80
55	60	65	70	80
18.5	22	26	30	39.5



42CrMo4/60 - 62 HRC

Non hardened radius bars of C45 steel (ground) are also available.

P10 RF-A

Round bars suitable for radius bar holder

Length	Ø Round bars	Part number
515 mm	28 mm	65200.0028.5002
	30 mm	65200.0030.5007
	35 mm	65200.0035.5005
	40 mm	65200.0040.5005
	45 mm	65200.0045.5003
	50 mm	65200.0050.5009
	55 mm	65200.0055.5002
	60 mm	65200.0060.5004
	65 mm	65200.0065.5002
	70 mm	65200.0070.5001
	80 mm	65200.0080.5003

1030 mm	28 mm	65200.0028.3002
	30 mm	65200.0030.3007
	35 mm	65200.0035.3002
	40 mm	65200.0040.3006
	45 mm	65200.0045.3002
	50 mm	65200.0050.3005
	55 mm	65200.0055.3001
	60 mm	65200.0060.3004
	65 mm	65200.0065.3001
	70 mm	65200.0070.3003
	80 mm	65200.0080.3004


P11 RF-A H175



[R] Radius (mm) -
Nose angle -
[H] Height (mm) 175

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1600 \text{ kN/m}$
- Operator side
- Head supported
- 26.7 kg/m
- Hydraulic clamping
-
- Ex stock / 24 h
- BOS No.** BY1C057

Standard length	Part number
515 mm	65206.0011.5004
1030 mm	65206.0011.3001
1000 mm sect. FSC	65206.0011.0002
1100 mm sect. FSL	65206.0011.1001



P11 RF-A
 $F = 1600 \text{ kN/m}$
 $H = 175 \text{ mm}$

P11 RF-A H250

Upper Tools


68



[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	250

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1600 \text{ kN/m}$
- Operator side
- Head supported
- 38.5 kg/m
- Hydraulic clamping
-
- Ex stock / 24 h
- BOS No.** BY1C058

Standard length	Part number
515 mm	65206.0011.5003
1030 mm	65206.0011.3002
1000 mm sect. FSC	65206.0011.0001
1100 mm sect. FSL	65206.0011.1002



P11 RF-A
 $F = 1600 \text{ kN/m}$
 $H = 250 \text{ mm}$

Upper Tools

69

P12 RF-A H130

Upper Tools

70




[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	130

Standard length	Part number
515 mm	65206.0012.5001
1030 mm	65206.0012.3002
1000 mm sect. FSC	65206.0012.0002
1100 mm sect. FSL	65206.0012.1001




H1 = 44 mm
H2 = 35mm
(standard)

P12 RF-A
F = 1600 kN/m
H = 130 mm



Typ B



Typ A

Upper Tools

71

P12 Radius tools

42CrMo4 hardened

Radius	Weight	Length	Part number
R= 5	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 6	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 8	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 10	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 12	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 15	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 20	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 25	Type B	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 30	Type B	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 35	Type B	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL

P12 Radius tools

C45 unhardened , ground

Radius	Weight	Length	Part number
R= 5	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R= 6	Type A	6,6 kg	515 mm
		13,1 kg	1030 mm
		12,7 kg	1000 mm SECT. FSC
		14,0 kg	1100 mm SECT. FSL
R=8	Type A	6,9 kg	515 mm
		13,8 kg	1030 mm
		13,4 kg	1000 mm SECT.
		14,8 kg	1100 mm SECT.
R=10	Type A	7,2 kg	515 mm
		14,4 kg	1030 mm
		14 kg	1000 mm SECT. FSC
		15,4 kg	1100 mm SECT. FSL
R=12	Type A	7,5 kg	515 mm
		14,9 kg	1030 mm
		14,5 kg	1000 mm SECT. FSC
		16,0 kg	1100 mm SECT. FSL
R=15	Type A	7,9 kg	515 mm
		15,7 kg	1030 mm
		15,2 kg	1000 mm SECT. FSC
		16,7 kg	1100 mm SECT. FSL
R=20	Type A	8,4 kg	515 mm
		16,7 kg	1030 mm
		16,2 kg	1000 mm SECT. FSC
		17,8 kg	1100 mm SECT. FSL
R= 25	Type B	4,8 kg	515 mm
		9,5 kg	1030 mm
		9,2 kg	1000 mm SECT. FSC
		10,1 kg	1100 mm SECT. FSL
R=30	Type B	7 kg	515 mm
		14,0 kg	1030 mm
		13,6 kg	1000 mm SECT. FSC
		15,0 kg	1100 mm SECT. FSL
R=35	Type B	9,5 kg	515 mm
		19,0 kg	1030 mm
		18,4 kg	1000 mm SECT. FSC
		20,3 kg	1100 mm SECT. FSL

P13 RF-A

Upper Tools

74



[R] Radius (mm) -

Nose angle -

[H] Height (mm)

42 CrMo 4

58 - 62 HRC

$F_{max} = 1000 \text{ kN/m}$

Operator side

Head supported

kg/m


Hydraulic clamping

Variable (Edge)

Ex stock / 24 h

BOS No. IB00674E

Combination between
Hämmerle + Xpert tools



Upper Tools

75

P13 RF-A

Overview

Model	Length	Part number
P13 RFA H1/ IB00674D	50 mm	65206.0013.5001
	55 mm	65206.0013.5002
	60 mm	65206.0013.5003
	65mm	65206.0013.5004
	Horn 70mm	65206.0013.5005
	80 mm	65206.0013.5006
	85 mm	65206.0013.5007
	90 mm	65206.0013.5008
	95 mm	65206.0013.5009
	100 mm	65206.0013.5010
	200 mm	65206.0013.5011
	500 mm	65206.0013.5012
	1000 mm sect.	65206.0013.0001
	75 mm	65206.0013.5039

1000 sect. = 50mm, 55mm, 60mm, 2x 65mm, 70mm Horn, 80mm, 90mm, 95mm, 100mm, 200mm

Model	Length	Part number
P13 RFA H2/ IB00696D	50 mm	65206.0013.5013
	55 mm	65206.0013.5014
	60 mm	65206.0013.5015
	65mm	65206.0013.5016
	Horn 70mm	65206.0013.5017
	80 mm	65206.0013.5018
	85 mm	65206.0013.5019
	90 mm	65206.0013.5020
	95 mm	65206.0013.5021
	100 mm	65206.0013.5022
	200 mm	65206.0013.5023
	500 mm	65206.0013.5024
	1000 mm sect.	65206.0013.0002
	75 mm	65206.0013.5038

1000 sect. = 50mm, 55mm, 60mm, 2x 65mm, 70mm Horn, 80mm, 90mm, 95mm, 100mm, 200mm

P13 RF-A

Overview

Model	Length	Part number
P13 RFA H3/ IB00697F	50 mm	65206.0013.5025
	55 mm	65206.0013.5026
	60 mm	65206.0013.5027
	65mm	65206.0013.5028
	Horn 70mm	65206.0013.5029
	80 mm	65206.0013.5030
	85 mm	65206.0013.5031
	90 mm	65206.0013.5032
	95 mm	65206.0013.5033
	100 mm	65206.0013.5034
	200 mm	65206.0013.5035
	500 mm	65206.0013.5036
	1000 mm sect.	65206.0013.0003
	75 mm	65206.0013.5037

1000 sect. = 50mm, 55mm, 60mm, 2x 65mm, 70mm Horn, 80mm, 90mm, 95mm, 100mm, 200mm

Adapter P25 Xpert/Euro B




[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	130/250
Length (mm)	150

Type	Height (mm)	Weight (kg / m)	Psr number
P25 R	105	16	64600.000.0072
P25 RF	130	20	64600.000.0072
P25 RF	200	31	64600.000.0073
P25 RF-A	130	20	64600.000.0033
P25 RF- A	250	38.8	64600.000.0037

- C45
-
- Fmax = 1600 kN/m
- Operator side
- Head supported
- see down below
- Xpert / variable
-
- Ex stock/ 24 h
- BOS No. ---

Example: R / Euro B



Extension P30



[R] Radius (mm) -

Nose angle -


[H] Height (mm) variable

Length (mm) 150



C45





$F_{max} = 1600 \text{ kN/m}$




Operator side



Head supported




see down below



Xpert / variable





Ex stock / 24 h




BOS
No.



Type	High H / H1 in mm	Weight in kg / m	Part number
P30 R	139/100	43	64600.0000.0025
P30 RF	184/125	46.9	64600.0000.0049
P30 RF	259/200	58.7	64600.0000.0039
P30 RF-A	184/125	46.9	64600.0000.0024
P30 RF-A	309/250	66.5	64600.0000.0032

Example: RF-A / RF



Bottom tools Xpert



Bottom tools Xpert


Recommendation starterkit Xpert 60 - 320

Bend length	Part number	Designation	Pieces	Unit
2050 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	4	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	2	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
2550 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	5	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	2	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
3100 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	6	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	3	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece
4100 mm	65206.0005.5007	Punch P5 RF-A/30° L=515	8	pieces
	65206.0005.0003	Punch P5 RF-A/30° L=1000 sect. FSC	1	piece
	64201.0012.3009	Die V12/30° L=1030	4	pieces
	64201.0012.0002	Die V12/30° L=1000 sect.FSC	1	piece

Lower table options


Tables with mechanical tool clamping

T5
(Standard Xpert 60 – 320)



Fitting bottom tools
up to V80.

T55
(Standard Xpert 250 – 1000)




Fitting bottom tools
up to V150.

Lower table options


Table with hydraulic tool clamping

T12
(Optional Xpert 60 - 320 and
Xpert 250 - 1000)



Fitting bottom tools
up to V80.

T13
(Optional Xpert 60 - 320 and
Xpert 250 - 1000)




Fitting bottom tools
up to V150.

Lower table options

Tables for larger bottom tools

T2

(Standard Xpert MAMMUT and
Optional Xpert 250 - 1000)*



Fitting bottom tools
up to V250.

* this table is ideal to use adapter's (for example S1),
large bottom tools or with V bottom tools.


Lower table options

Hydraulic dutch bending table


T8

(Optional for Xpert 60 - 320, but only on special request)

up to 3mm mild steel thickness



open



closed


Lower table options

Hydraulic dutch bending table with hydraulic die clamping

T9

(Optional for Xpert 60 - 320)

up to 2mm material thickness



This table combines the high productivity of the hydraulic tool clamping with the flexibility of dutch bending.

Lower die options

Bottom tool segmentation

Segmentation FSC/1000 mm

(10 + 15 + 20 + 30 + 50 + 100 + 200 + 275 + 300)

	10	15	20	30	50	100	200	275	300
--	----	----	----	----	----	-----	-----	-----	-----

FSL/1100 mm

(10 + 15 + 20 + 30 + 50 + 100 + 200 + 375 + 300)

	10	15	20	30	50	100	200	375	300
--	----	----	----	----	----	-----	-----	-----	-----


Special segmentation on request.

In addition all lower dies can be supplied with modified radii, die angle and height (non standard).

V6/30°

[R] Radius (mm)	0.75
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	20
[D] Depth (mm)	9.3
Weight / Meter	10.9 Kg


Standard length	Part number
515 mm	64201.0006.5004
1030 mm	64201.0006.3008
1000 mm sect. FSC	64201.0006.0001
1100 mm sect. FSL	64201.0006.1002

**V8/30°**

[R] Radius (mm)	1
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	20
[D] Depth(mm)	11.2
Weight / Meter	10.8 Kg

Standard length	Part number
515 mm	64201.0008.5012
1030 mm	64201.0008.3005
1000 mm sect. FSC	64201.0008.0001
1100 mm sect. FSL	64201.0008.1002

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max\ 30^\circ} = 400\ kN/m$
- $F_{max\ 90^\circ} = 800\ kN/m$
- Die insert 13 mm
- Ex stock / 24 h
- BOS No. BY2C001




- 42 CrMo 4
- 58 - 62 HRC
- $F_{max\ 30^\circ} = 300\ kN/m$
- $F_{max\ 90^\circ} = 1000\ kN/m$
- Sie insert 13 mm
- Ex Stock / 24 h
- BOS No. BY2C007

V10/30°

[R] Radius (mm)	1
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	20
[D] Depth (mm)	14.9
Weight / Meter	10.6 Kg

Standard length	Part number
515 mm	64201.0010.5016
1030 mm	64201.0010.3006
1000 mm sect. FSC	64201.0010.0004
1100 mm sect. FSL	64201.0010.1002




- 42 CrMo 4
- 58 - 62 HRC
- F max 30° = 200 kN/m
- F max 90° = 700 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY2C013


V12/30°

[R] Radius (mm)	1.5
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	25
[D] Depth (mm)	18.6
Weight / Meter	11.8 Kg

Standard length	Part number
515 mm	64201.0012.5007
1030 mm	64201.0012.3009
1000 mm sect. FSC	64201.0012.0002
1100 mm sect. FSL	64201.0012.1002




- 42 CrMo 4
- 58 - 62 HRC
- F max 30° = 250 kN/m
- F max 90° = 900 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY2C016A

V16/30°

[R] Radius (mm)	2
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	30
[D] Depth (mm)	20.5
Weight / Meter	13.3 Kg

Standard length	Part number
515 mm	64201.0016.5011
1030 mm	64201.0016.3006
1000 mm sect. FSC	64201.0016.0001
1100 mm sect. FSL	64201.0016.1002

- 42 CrMo 4
- 58 - 62 HRC
- F max 30° = 250 kN/m
- F max 90° = 1000 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY2C019

V20/30°


[R] Radius (mm)	2.5
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	30
[D] Depth (mm)	28
Weight / Meter	12.2 Kg

Standard length	Part number
515 mm	64201.0020.5002
1030 mm	64201.0020.3007
1000 mm sect. FSC	64201.0020.0002
1100 mm sect. FSL	64201.0020.1001

- 42 CrMo 4
- 58 - 62 HRC
- F max 30° = 150 kN/m
- F max 90° = 600 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY20002

V24/30°

96



[R] Radius (mm)	3
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	40
[D] Depth (mm)	29.8
Weight / Meter	15.5 Kg

Standard length	Part number
515 mm	64201.0024.5010
1030 mm	64201.0024.3005
1000 mm sect. FSC	64201.0024.0001
1100 mm sect. FSL	64201.0024.1002



42 CrMo 4



58 - 62 HRC



F max 30° = 300 kN/m



F max 90° = 1100 kN/m



Die insert 13 mm




Ex stock / 24 h



BY2C020

V32/30° *

97



[R] Radius (mm)	4
[a] V - Angle	30°
[H] Height (mm)	55
[B] Width (mm)	48
[D] Depth (mm)	33.6
Weight / Meter	16.7 Kg

Standard length	Part number
515 mm	64201.0032.5010
1030 mm	64201.0032.3006
1000 mm sect. FSC	64201.0032.0002
1100 mm sect. FSL	64201.0032.1002



42 CrMo 4



58 - 62 HRC



F max 30° = 300 kN/m



F max 90° = 1100 kN/m



Die insert 13 mm



Ex stock / 24 h




BY2C021

* Also available with rolls.

V40/60° *

98




[R] Radius (mm)	5
[a] V - Angle	60°
[H] Height (mm)	55
[B] Width (mm)	55
[D] Depth (mm)	29.6
Weight / Meter	20.5 Kg

Standard length	Part number
515 mm	64201.0040.5003
1030 mm	64201.0040.3007
1000 mm sect. FSC	64201.0040.0002
1100 mm sect. FSL	64201.0040.1001

* Also available with rolls.

V50/60° *

99



[R] Radius (mm)	5
[a] V - Angle	60°
[H] Height (mm)	55
[B] Width (mm)	70
[D] Depth (mm)	30.3
Weight / Meter	24.5 Kg


Standard length	Part number
515 mm	64201.0050.5003
1030 mm	64201.0050.3003
1000 mm sect. FSC	64201.0050.0001
1100 mm sect. FSL	64201.0050.1001

* Also available with rolls.

42 CrMo 4
58 - 62 HRC
F max 60° = 1000 kN/m
F max 90° = 1800 kN/m
Die insert 13 mm
Ex stock / 24 h
BY2C022

V60/60° *

100




[R] Radius (mm)	7
[a] V - Angle	60°
[H] Height (mm)	65
[B] Width (mm)	80
[D] Depth (mm)	39
Weight / Meter	31.4 Kg

Standard length	Part number
515 mm	64201.0060.5005
1030 mm	64201.0060.3005
1000 mm sect. FSC	64201.0060.0002
1100 mm sect. FSL	64201.0060.1001

* Also available with rolls.

V80/80° *

101



[R] Radius (mm)	10
[a] V - Angle	80°
[H] Height (mm)	65
[B] Width (mm)	100
[D] Depth (mm)	38.7
Weight / Meter	38.6 Kg


Standard length	Part number
515 mm	64201.0080.5002
1030 mm	64201.0080.3005
1000 mm sect. FSC	64201.0080.0001
1100 mm sect. FSL	64201.0080.1002

* Also available with rolls.

- 42 CrMo 4
- 58 - 62 HRC
- F_{max} 60° = 900 kN/m
- F_{max} 90° = 1600 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY2C024
- 42 CrMo 4
- 58 - 62 HRC
- F_{max} 80° = 1400 kN/m
- F_{max} 90° = 1600 kN/m
- Die insert 13 mm
- Ex stock / 24 h
- BY2C025

V100/80° *

102



[R] Radius (mm)	12
[a] V - Angle	80°
[H] Height (mm)	85
[B] Width (mm)	125
[D] Depth (mm)	50.5
Weight / Meter	62.5 Kg

Standard length	Part number
515 mm	64201.0100.5004
1030 mm	64201.0100.3005
1000 mm sect. FSC	64201.0100.0001
1100 mm sect. FSL	64201.0100.1001

* Also available with rolls.



42 CrMo 4



58 - 62 HRC



F max 80° = 1800 kN/m



F max 90° = 2000 kN/m



Die insert 13 mm




Ex stock / 24 h



BY2C026

V120/80° *

103



[R] Radius (mm)	15
[a] V - Angle	80°
[H] Height (mm)	105
[B] Width (mm)	160
[D] Depth (mm)	59.5
Weight / Meter	101 Kg

Standard length	Part number
515 mm	64201.0120.5002
1030 mm	64201.0120.3004
1000 mm sect. FSC	64201.0120.0001
1100 mm sect. FSL	64201.0120.1001



42 CrMo 4



58 - 62 HRC



F max 80° = 2000 kN/m



F max 90° = 2400 kN/m



Die insert 13 mm



Ex stock / 24 h



BY2C027

* Also available with rolls.


S1/73

104



[R] Radius (mm)	-
V - Angle	-
[H] Height (mm)	73
[B] Width (mm)	58
[D] Depth (mm)	22
Weight / Meter	33 Kg

Standard length	Part number
515 mm	64201.0001.5008
1030 mm	64201.0001.3003
1000 mm sect. FSC	64201.0001.0003
1100 mm sect. FSL	64201.0001.1001


**S1/100**

105



[R] Radius (mm)	-
V - Angle	-
[H] Height (mm)	100
[B] Width (mm)	58
[D] Depth (mm)	22
Weight / Meter	45.3 Kg

Standard length	Part number
515 mm	64201.0001.5006
1030 mm	64201.0001.3004
1000 mm sect. FSC	64201.0001.0001
1100 mm sect. FSL	64201.0001.1002



C45

$F_{max} = 5000 \text{ kN/m}$
Die insert 13 mm
Ex stock / 24 h
BOS No. BY40002

C45

$F_{max} = 5000 \text{ kN/m}$
Die insert 13 mm
Ex stock / 24 h
BOS No. BY40003


Hemming tools air bending

Hemming tool P900 (upper tool)


P900

L = 515 / 1030 S = 1000 / 1100 R = 1 α = 30°

	P900 R			P900 RF			P900 RF-A		
H	175			175			175		
B	6	8	10	6	8	10	6	8	10
G	22	22.8	21	24	24.6	25.2	23	24.4	25
F	500	700	1000	500	700	1000	500	700	1000



P900 and V900



Material thickness mm	Required press force t/m	C mm	Required press force t/m	D mm
0.6	9	3.0	32	1.2
0.8	13	3.0	34	1.6
1.0	15	3.5	36	2.0
1.2	18	3.5	46	2.4
1.6	24	3.5	48	3.2
2.0	42	4.5	52	4.0

L = length (mm)
 S = sectionalized (mm)
 Z = width (mm)
 R = radius (mm)
 H = Height (mm)
 B = nose width (mm)
 W = die opening (mm)
 G = weight (kg/m)
 F = max. permissible load (kN/m)

Hemming tools air bending

Hemming tool P900 (upper tool)

107

Mod.	B mm	Z	L mm	Part number
P900.RFA.06	6	14	515	65206.0900.5013
P900.RFA.06	6	14	1030	65206.0900.3004
P900.RFA.06	6	14	1000 S	65206.0900.0010
P900.RFA.06	6	14	1100 S	65206.0900.1005
P900.RFA.08	8	13	515	65206.0900.5005
P900.RFA.08	8	13	1030	65206.0900.3002
P900.RFA.08	8	13	1000 S	65206.0900.0002
P900.RFA.08	8	13	1100 S	65206.0900.1002
P900.RFA.10	10	12	515	65206.0900.5004
P900.RFA.10	10	12	1030	65206.0900.3005
P900.RFA.10	10	12	1000 S	65206.0900.0004
P900.RFA.10	10	12	1100 S	65206.0900.1003
P900.RFA.12	12	11	515	65206.0900.5007
P900.RFA.12	12	11	1030	65206.0900.3003
P900.RFA.12	12	11	1000 S	65206.0900.0003
P900.RFA.12	12	11	1100 S	65206.0900.1004

Loading capacity of the tools (bending forces) P900 + V900:

Pre bending step: 25 t/m

Hemming step: 50 t/m

B=6 mm -> for sheet thickness up to 1,0 mm

B=8 mm -> for sheet thickness up to 1,5 mm

B=10 mm -> for sheet thickness up to 2,0 mm

B=12 mm -> for sheet thickness up to 2,3 mm


Hemming tools air bending

Hemming tool V900 (bottom tool)


V900

L = 515 / 1030 S = 1000 / 1100

V900				
H	85			
W	6	8	10	12
G	36.5	37	38	39
F				
500				



P900 and V900



Material thickness mm	Required press force t/m	C mm	Required press force t/m	D mm
0.6	9	3.0	32	1.2
0.8	13	3.0	34	1.6
1.0	15	3.5	36	2.0
1.2	18	3.5	46	2.4
1.6	24	3.5	48	3.2
2.0	42	4.5	52	4.0

L = length (mm)
 S = sectionalized (mm)
 Z = width (mm)
 R = radius (mm)
 H = high (mm)
 B = nose width (mm)
 W = die opening (mm)
 G = weight (kg/m)
 F = max. permissible load (kN/m)

Hemming tools air bending

Hemming tool V900 (bottom tool)

109

Mod.	W mm	R mm	L mm	Part number
V900.06	6	1	515	64201.0900.5010
V900.06	6	1	1030	64201.0900.3007
V900.06	6	1	1000 S	64201.0900.0006
V900.06	6	1	1100 S	64201.0900.1004
V900.08	8	1	515	64201.0900.5005
V900.08	8	1	1030	64201.0900.3003
V900.08	8	1	1000 S	64201.0900.0002
V900.08	8	1	1100 S	64201.0900.1002
V900.10	10	1	515	64201.0900.5004
V900.10	10	1	1030	64201.0900.3004
V900.10	10	1	1000 S	64201.0900.0004
V900.10	10	1	1100 S	64201.0900.1003
V900.12	12	1	515	64201.0900.5007
V900.12	12	1	1030	64201.0900.3006
V900.12	12	1	1000 S	64201.0900.0003
V900.12	12	1	1100 S	64201.0900.1005

Loading capacity of the tools (bending forces) P900 + V900:

Pre bending step: 25 t/m

Hemming step: 50 t/m

B=6 mm -> for sheet thickness up to 1,0 mm

B=8 mm -> for sheet thickness up to 1,5 mm

B=10 mm -> for sheet thickness up to 2,0 mm

B=12 mm -> for sheet thickness up to 2,3 mm

Upper tools Xcel / Xact



Upper tools Xcel / Xact

Recommendation starterkit Xcel

Bend length	Part number	Designation	Pieces	Unit
1600 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	1	piece
	65035.1012.3003	Punch 1012/35° R=0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	1	piece
	65088.1014.3003	Punch 1014/88° R=0,8 L=835 EURO-B sect	1	piece
	64201.0012.507	Die V12/30° L=515	1	piece
	64201.0012.1002	Die V12/30° L=1100 sect.FSL	1	piece

Recommendation starterkit Xact


Bend length	Part number	Designation	Pieces	Unit
3100 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	3	pieces
	65035.1012.3003	Punch 1012/35° R=0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	3	pieces
	65088.1014.3003	Punch 1014/88° R=0,8 L=835 EURO-B sect	1	piece
	64201.0016.5011	Die V16/30° L=515	4	pieces
	64201.0016.1002	Die V16/30° L=1100 sect.FSL	1	piece
4100 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	4	pieces
	65035.1012.3003	Punch 1012/35° R=0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	4	pieces
	65088.1014.3003	Punch 1014/88° R=0,8 L=835 EURO-B sect	1	piece
	64201.0016.5011	Die V16/30° L=515	6	pieces
	64201.0016.1002	Die V16/30° L=1100 sect.FSL	1	piece

Recommendation upper tools


112

Clamping Euro B

Euro B mechanical
(Standard Xact)



Euro B hydraulic
(Optional Xact)




Recommendation upper tools

Upper tools segmentation

113

Segmentation 835 mm
(10 / 15 / 20 / 40 / 50 / (2 x 100) / 200 / 300)



Special segmentation available on request.



$\leq 800 \text{ kN/m}$



sideway insertion




shoulder supported



mechanical and hydraulic

10.10





[R] Radius (mm) 0.2/0.8/3


Nose Angle 88°

[H] Height (mm) 67/66.7/65.7

[B] Width (mm) 26



10.116





[R] Radius (mm) 0.2

Nose angle 88°/90°

[H] Height (mm) 67


[B] Width (mm) 26



Standard length	Part number
415 mm / 835 mm R = 0.2	65088.1010.4008 / 65088.1010.4007
835 mm sect. R = 0.2	65088.1010.3003
415 mm / 835 mm R = 0.8	65088.1010.4002 / 65088.1010.4001
835 mm sect. R = 0.8	65088.1010.3001
415 mm / 835 mm R = 3	65088.1010.4004 / 65088.1010.4003
835 mm sect. R = 3	65088.1010.3002

Standard length	Part number
415 mm 88°	65088.1116.4001
835 mm 88°	65088.1116.4002
835 mm sect. 88°	65088.1116.3001
415 mm 90°	65090.1116.4001
835 mm 90°	65090.1116.4002
835 mm sect. 90°	65090.1116.3001

10.14



C45

54 - 56 HRC

$F_{max} = 500 \text{ kN/m}$

Sideways insertion

Shoulder supported

25 kg/m

Euro B

37.1 mm

Ex stock / 24 h

[R] Radius (mm) 0.2/0.8/3

Nose angle 88°


[H] Height (mm) 90/89.7/88.7

[B] Width (mm) 56

IA00069/IA00009/IA00148

Standard length	Part number
415 mm / 835 mm R = 0.2	65088.1014.4009 / 65088.1014.4010
835 mm sect. R = 0.2	65088.1044.3005
415 mm / 835 mm R = 0.8	65088.1014.4006 / 65088.1014.4005
835 mm sect. R = 0.8	65088.1014.3003
415 mm / 835 mm R = 3	65088.1014.4004 / 65088.1014.4003
835 mm sect. R = 3	65088.1014.3002

10.15



C45

54 - 56 HRC

$F_{max} = 500 \text{ kN/m}$

Sideways insertion

Shoulder supported

26.7 kg/m

Euro B

47.6 mm

Ex stock / 24 h

[R] Radius (mm) 0.2/0.8/3


Nose angle 88°

[H] Height (mm) 105/104.7/103.7

[B] Width (mm) 56

IA00082/IA00033/IA00080

Standard length	Part number
415 mm / 835 mm R = 0.2	65088.1015.4013 / 65088.1015.4014
835 mm sect. R = 0.2	65088.1015.3006
415 mm / 835 mm R = 0.8	65088.1015.4004 / 65088.1015.4003
835 mm sect. R = 0.8	65088.1015.3002
415 mm / 835 mm R = 3	65088.1015.4006 / 65088.1015.4005
835 mm sect. R = 3	65088.1015.3003

10.047

C45

54 - 56 HRC

$F_{max} = 500 \text{ kN/m}$

Sideways insertion

Shoulder supported

31.5 kg/m

Euro B

58.8 mm

Ex stock / 24 h

[R] Radius (mm) 0.2/0.8


Nose angle 88°

[H] Height (mm) 120/119.7

[B] Width (mm) 65

IA00104/IA00105

Standard length	Part number
415 mm / 835 mm R = 0.2	65088.1047.4004 / 65088.1047.4001
835 mm sect. R = 0.2	65088.1047.3001
415 mm / 835 mm R = 0.8	65088.1047.4005 / 65088.1047.4006
835 mm sect. R = 0.8	65088.1047.3003

10.048

C45

54 - 56 HRC

$F_{max} = 500 \text{ kN/m}$

Sideways insertion

Shoulder supported

31.5 kg/m

Euro B

58.8 mm

Ex stock / 24 h

IA00100


[R] Radius (mm) 0.2

Nose angle 90°

[H] Height (mm) 120

[B] width (mm) 65

Standard length	Part number
415 mm / 835 mm R = 0.2	65090.1048.4001 / 65090.1048.4002
835 mm sect. R = 0.2	65090.1048.3001
415 mm / 835 mm R = 0.8	65090.1048.4003 / 65090.1048.4004
835 mm sect. R = 0.8	65090.1048.3002

10.109

[R] Radius (mm) 0.2


Nose angle 88°/90°

[H] Height (mm) 95

[B] Width (mm) 27



54 - 56 HRC



Sideways insertion




11.5 kg/m



42.0 mm



BOS No. IA00443

10.18

[R] Radius (mm) 0.8


Nose angle 26°

[H] Height (mm) 117

[B] Width (mm) 27



54 - 56 HRC



Sideways insertion



16 kg/m



57.4 mm




BOS No. IA00519

Standard length	Part number
415 mm 88°	65088.1109.4002
835 mm 88°	65088.1109.4001
835 mm sect. 88°	65088.1109.3010
415 mm 90°	65090.1109.4001
835 mm 90°	65090.1109.4002
835 mm sect. 90°	65090.1109.3001

Standard length	Part number
415 mm R = 0.8	65026.1018.4002
835 mm R = 0.8	65026.1018.4001
835 mm sect. R = 0.8	65026.1018.3001

10.12




[R] Radius (mm)	0.8
Nose angle	35°/30°
[H] Height (mm)	90
[B] width (mm)	26

- C45
- 54 - 56 HRC
- F_{max} = 500 kN/m
- Sideways insertion
- Shoulder supported
- 14.5/14 kg/m
- Euro B
- 38.5 mm
- Ex stock / 24 h
- BOS No. IA00001/IA00050

Standard length	Part number
415 mm 35°	65035.1012.4004
835 mm 35°	65035.1012.4003
835 mm sect. 35°	65035.1012.3003
415 mm 30°	65030.1012.4009
835 mm 30°	65030.1012.4005
835 mm sect. 30°	65030.1012.3003


10.13/35°





[R] Radius (mm)	5
Nose angle	35°
[H] Height (mm)	65
[B] width (mm)	34

- C45
- 54 - 56 HRC
- F_{max} = 800 kN/m
- Sideways insertion
- Shoulder supported
- 15 kg/m
- Euro B
- 21.0 mm
- Ex stock / 24 h
- BOS No. IA00010

Standard length	Part number
415 mm	65035.1013.4002
835 mm	65035.1013.4001
835 mm sect.	65035.1013.3001


10.13/60°

[R] Radius (mm)	6
Nose angle	60°
[H] Height (mm)	65
[B] width (mm)	36



Standard length	Part number
415 mm	65060.1013.4001
835 mm	65060.1013.4003
835 mm sect.	65060.1013.3001

Bottom tools Xcel / Xact



Bottom tools Xcel / Xact

Recommendation starterkit Xcel

Bend length	Part number	Designation	Pieces	Unit
1600 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	1	piece
	65035.1012.3003	Punch 1012/35° R0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	1	piece
	65088.1014.3003	Punch 1014/88° R0,8 L=835 EURO-B sect	1	piece
	64201.0012.507	Die V12/30° L=515	1	piece
	64201.0012.1002	Die V12/30° L=1100 sect.FSL	1	piece

Recommendation starterkit Xact

Bend length	Part number	Designation	Pieces	Unit
3100 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	3	pieces
	65035.1012.3003	Punch 1012/35° R0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	3	pieces
	65088.1014.3003	Punch 1014/88° R0,8 L=835 EURO-B sect	1	piece
	64201.0016.5011	Die V16/30° L=515	4	pieces
	64201.0016.1002	Die V16/30° L=1100 sect.FSL	1	piece
4100 mm	65035.1012.4003	Punch 1012/35° R=0,8 L=835 EURO-B	4	pieces
	65035.1012.3003	Punch 1012/35° R0,8 L=835 EURO-B sect	1	piece
	65088.1014.4005	Punch 1014/88° R=0,8 L=835 EURO-B	4	pieces
	65088.1014.3003	Punch 1014/88° R0,8 L=835 EURO-B sect	1	piece
	64201.0016.5011	Die V16/30° L=515	6	pieces
	64201.0016.1002	Die V16/30° L=1100 sect.FSL	1	piece


Recommendation bottom tools

128

Table T21

Table T21
(Standard Xact)

Can accept both Xpert single vee lower dies and Euro B lower dies.




Recommendation bottom tools

Segmentation

129


Segmentation 835 mm
(10 / 15 / 20 / 40 / 50 / 2 x 100 / 200 / 300)



Special segmentation available on request.

V 6 Type 20.41/88/90

130



[R] Radius (mm) 0.5/0.4

V - Angle 88°/90°

[H] Height (mm) 80

[B] Width (mm) 60



C45



54 - 56 HRC



Fmax = 500 kN/m



15.2 kg/m



T - die 60mm



Ex stock / 24 h



IA00182/IA00183

Standard length Part number

415 mm 88° 64060.2041.0004

835 mm 88° 64088.2041.0002

835 mm sect. 88° 64088.2041.0003


415 mm 90° 64090.2041.1001

835 mm 90° 64090.2041.1002

835 mm sect. 90° 64090.2041.0001

V 6 Type 20.41/60

131



[R] Radius (mm) 0.5

V - Angle 60°

[H] Height (mm) 80

[B] Width (mm) 60



C45



54 - 56 HRC



Fmax = 400 kN/m



15 kg/m



T - die 60mm



Ex stock / 24 h



IA00181

Standard length Part number


415 mm 60° 64060.2041.1003

835 mm 60° 64060.2041.1004

835 mm sect. 60° 64060.2041.0001




V 6 Type 20.41/35/30

132




[R] Radius (mm)	1
V - Angle	35°/30°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 35°	64035.2041.1002
835 mm 35°	64035.2041.1003
835 mm sect. 35°	64035.2041.0001
415 mm 30°	64030.2041.1002
835 mm 30°	64030.2041.1001
835 mm sect. 30°	64030.2041.0001



**V 8 Type 20.42/88/90**


133



[R] Radius (mm)	0.5
V - Angle	88°/90°
[H] Height (mm)	80
[B] Width (mm)	60


Standard length	Part number
415 mm 88°	64088.2042.1002
835 mm 88°	64088.2042.1003
835 mm sect. 88°	64088.2042.0002
415 mm 90°	64090.2042.1001
835 mm 90°	64090.2042.1002
835 mm sect. 90°	64090.2042.0001



V 8 Type 20.42/60


[R] Radius (mm)	0.8
V - Angle	60°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 60°	64060.2042.1004
835 mm 60°	64060.2042.1003
835 mm sect. 60°	64060.2042.0001

**V 8 Type 20.42/35/30**


[R] Radius (mm)	1
V - Angle	35°/30°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 35°	64035.2042.1007
835 mm 35°	64035.2042.1006
835 mm sect. 35°	64035.2042.0002
415 mm 30°	64030.2042.1001
835 mm 30°	64030.2042.1002
835 mm sect. 30°	64030.2042.0001





V 10 Type 20.43/88/90

136




[R] Radius (mm)	0.6
V - Angle	88°/90°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 88°	64088.2043.1002
835 mm 88°	64088.2043.1001
835 mm sect. 88°	64088.2043.0001
415 mm 90°	64090.2043.1001
835 mm 90°	64090.2043.1002
835 mm sect. 90°	64090.2043.0001


**V 10 Type 20.43/60**


137



[R] Radius (mm)	1
V - Angle	60°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 60°	64060.2043.1003
835 mm 60°	64060.2043.1001
835 mm sect. 60°	64060.2043.0001




V 10 Type 20.43/35/30

[R] Radius (mm)	1
V - Angle	35°/30°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 35°	64035.2043.1006
835 mm 35°	64035.2043.1005
835 mm sect. 35°	64035.2043.0002
415 mm 30°	64030.2043.1002
835 mm 30°	64030.2043.1001
835 mm sect. 30°	64030.2043.0001

- C45
- 54 - 56 HRC
- Fmax = 130/180 kN/m
- 17.5 kg/m
- T - die 60mm
- Ex stock / 24 h
- IA00007/IA00190

V 12 Type 20.44/88/90


[R] Radius (mm)	0.8
V - Angle	88°/90°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 88°	64088.2044.1006
835 mm 88°	64088.2044.1005
835 mm sect. 88°	64088.2044.0002
415 mm 90°	64090.2044.1002
835 mm 90°	64090.2044.1001
835 mm sect. 90°	64090.2044.0001

- C45
- 54 - 56 HRC
- Fmax = 500 kN/m
- 16.9 kg/m
- T - die 60mm
- Ex stock / 24 h
- IA00021/IA00197

V 12 Type 20.44/60

140



[R] Radius (mm) 1.5

V - Angle 60°

[H] Height (mm) 80

[B] Width (mm) 60



C45



54 - 56 HRC



Fmax = 450 kN/m



16.7 kg/m



T - die 60mm



Ex stock / 24 h



BOS No. IA00340

Standard length Part number


415 mm 60° 64060.2044.1007

835 mm 60° 64060.2044.1006

835 mm sect. 60° 64060.2044.0001

V 12 Type 20.44/35/30

141



[R] Radius (mm) 1.5

V - Angle 35°/30°

[H] Height (mm) 80

[B] Width (mm) 60



C45



54 - 56 HRC



Fmax = 500 kN/m



19 kg/m



T - die 60mm




Ex stock / 24 h



BOS No. IA00195/IA00194



V 16 Type 20.45/88/90

142




[R] Radius (mm)	2.5
V - Angle	88°/90°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 88°	64088.2045.1002
835 mm 88°	64088.2045.1001
835 mm sect. 88°	64088.2045.0001
415 mm 90°	64090.2045.1002
835 mm 90°	64090.2045.1001
835 mm sect. 90°	64090.2045.0001


**V 16 Type 20.45/60**

143




[R] Radius (mm)	2
V - Angle	60°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 60°	64060.2045.1003
835 mm 60°	64060.2045.1002
835 mm sect. 60°	64060.2045.0001



V 16 Type 20.45/35/30

144



[R] Radius (mm)	2.0
V - Angle	35°/30°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 35°	64035.2045.1004
835 mm 35°	64035.2045.1005
835 mm sect. 35°	64035.2045.0002
415 mm 30°	64030.2045.1004
835 mm 30°	64030.2045.1002
835 mm sect. 30°	64030.2045.0002



C45



54 - 56 HRC



Fmax = 200/250 kN/m



20.5/21.4 kg/m



T - die 60mm




Ex stock / 24 h



IA00199/IA00198

V 20 Type 20.46/88/90

145



[R] Radius (mm)	3
V - Angle	88°/90°
[H] Height (mm)	80
[B] Width (mm)	60



C45



54 - 56 HRC



Fmax = 800 kN/m



22.2 kg/m



T - die 60mm





Ex stock / 24 h



IA00206/IA00207

V 20 Type 20.46/60

146




[R] Radius (mm)	2
V - Angle	60°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 60°	64060.2046.1007
835 mm 60°	64060.2046.1006
835 mm sect. 60°	64060.2046.0002


**V 20 Type 20.46/35/30**

147




[R] Radius (mm)	1.5
V - Angle	35°/30°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 35°	64035.2046.4002
835 mm 35°	64035.2046.4001
835 mm sect. 35°	64035.2046.3001
415 mm 30°	64030.2046.1002
835 mm 30°	64030.2046.1001
835 mm sect. 30°	64030.2046.0001




V 25 Type 20.47/85

148




[R] Radius (mm)	3
V - Angle	85°
[H] Height (mm)	80
[B] Width (mm)	60

Standard length	Part number
415 mm 85°	64085.2047.1002
835 mm 85°	64085.2047.1001
835 mm sect. 85°	64085.2047.0001


**V 32 Type 20.11/85**

149




[R] Radius (mm)	4
V - Angle	85°
[H] Height (mm)	60
[B] Width (mm)	60

Standard length	Part number
415 mm 85°	64085.2011.1048
835 mm 85°	64085.2011.1043
835 mm sect. 85°	64085.2011.0003





V 40 Type 20.11/85

150




[R] Radius (mm)	4
V - Angle	85°
[H] Height (mm)	60
[B] Width (mm)	60

Standard length	Part number
415 mm 85°	64085.2011.1049
835 mm 85°	64085.2011.1035
835 mm sect. 85°	64085.2011.0005



**V 50 Type 20.11/85**

151




[R] Radius (mm)	4
V - Angle	85°
[H] Height (mm)	60
[B] Width (mm)	60

Standard length	Part number
415 mm 85°	64085.2011.1037
835 mm 85°	64085.2011.1038
835 mm sect. 85°	64085.2011.0004



V 63 Type 20.11/85

152



[R] Radius (mm)	5
V - Angle	85°
[H] Height (mm)	75
[B] Width (mm)	80

Standard length	Part number
415 mm 85°	64085.2011.1041
835 mm 85°	64085.2011.1040
835 mm sect. 85°	64085.2011.0006



C45



54 - 56 HRC



Fmax = 500 kN/m



34.8 kg/m



T - die 60mm




Ex stock / 24 h



IA00004

V 80 Type 20.11/85

153



[R] Radius (mm)	5
V - Angle	85°
[H] Height (mm)	80
[B] Width (mm)	95

Standard length	Part number
415 mm 85°	64085.2011.1039
835 mm 85°	64085.2011.1036
835 mm sect. 85°	64085.2011.0007



C45



54 - 56 HRC



Fmax = 500 kN/m



40 kg/m



T - die 60mm




Ex stock / 24 h



IA00005

V 100 Type 20.11/85

154



[R] Radius (mm)	8
V - Angle	85°
[H] Height (mm)	95
[B] Width (mm)	115

Standard length	Part number
415 mm 85°	64085.2011.1044
835 mm 85°	64085.2011.1042
835 mm sect. 85°	64085.2011.0008



C45



54 - 56 HRC



Fmax = 500 kN/m



54.7 kg/m



T - die 60mm




Ex stock / 24 h



IA00018

V 125 Type 20.11/85

155



[R] Radius (mm)	15
V - Angle	80°
[H] Height (mm)	103
[B] Width (mm)	154

Standard length	Part number
415 mm 85°	64085.2011.1050
835 mm 85°	64085.2011.1047
835 mm sect. 85°	64085.2011.0009



C45



54 - 56 HRC



Fmax = 500 kN/m



81 kg/m



T - die 90mm




Ex stock / 24 h



IA00581

V 160 Type 20.11/85

156



[R] Radius (mm)	15
V - Angle	80°
[H] Height (mm)	130
[B] Width (mm)	185

Standard length	Part number
415 mm 85°	64085.2011.1051
835 mm 85°	64085.2011.1052
835 mm sect. 85°	64085.2011.0010



C45



54 - 56 HRC



Fmax = 800 kN/m



149 kg/m



T - die 90mm




Ex stock / 24 h



IA00164

Multi-V 16/22/35/50 Type 20.09

157



[R] Radius (mm)	2
V - Angle	85°/88°
[H] Height (mm)	
[B] Width (mm)	60

Standard length	Part number
415 mm	64000.2009.1005
835 mm	64000.2009.1010
835 mm sect.	64000.2009.0003



C45



54 - 56 HRC



Fmax = 500 kN/m



19 kg/m



T - die 60mm




Ex stock / 24 h





IA00159

Hemming tools V 10 Type 30.01/26/35




[R] Radius (mm)	1
V - Angle	26°/35°
[H] Height (mm)	~136
[B] Width (mm)	60



Standard length	Part number
415 mm 26°	64026.3001.1005
835 mm 26°	64026.3001.1006
sekt. 835 mm 26°	64026.3001.0001
415 mm 35°	64035.3001.1007
835 mm 35°	64035.3001.1005
sekt. 835 mm 35°	64035.3001.0001



Hemming tool V 12 Type 30.01/26/35



[R] Radius (mm)	1.5
V - Angle	26°/35°
[H] Height (mm)	~136
[B] Width (mm)	60



3P - bending

Upper tools 3-point-bending



Upper tools 3-point-bending

Recommendation starterkit Hämmerle 3P

Bend length	Part number	Description	Piece	Unit
2100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	17	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	3	pieces
3100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	27	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	5	pieces
4100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	37	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	7	pieces

Calculation basics 3-point-bending

Pressing force table

Ri (mm)	1	1.2	1.2	1.4	1.6	2	2.2
B (mm)	4	5.5	5.5	6.5	8	9	10
Die	31.005.00	31.006.00	31.007.00	31.007.20	31.010.20	31.012.00	31.013.00
V (mm)	5.0	6.0	7.0	7.5	10.9	11.5	12
t (mm)	Approx. capacity required in kN/m for mild steel plates with a tensile strength of Rm = 450 N/mm ²						
0.5	29	24					
0.8	75	62	53	50	34		
1.0	117	97	84	78	54	51	49
1.25		152	131	122	84	79	76
1.5			188	175	121	114	110
2.0				215	203	195	
2.5					335	318	305
3.0						458	439
3.5							
4.0							
5.0							
6.0							
7.0							
8.0							
10.0							
12.0							
$F = 450 \times \frac{t^2}{V} \times f = \dots \text{kN/m}$ [t (mm), V (mm)]							
Factor f	M.S.	1,3	S.S. 1,66	Alu 0,5			

Ri = approx. inner radius
B = smallest flange for 90° bends
V = die opening
t = material thickness

Calculation basics 3-point-bending

Pressing force table



2.7	3	3.9	4.1	6	9.5	15.5	18
12.5	16	19.5	23.5	30	45.5	70	85
31.016.00	31.021.00	31.024.00	31.032.10	31.040.10	31.060.00	31.090.00	31.110.00
16	21	25.6	32.1	39.2	60	90	110

Approx. capacity required in kN/m for mild steel plates with a tensile strength of Rm = 450 N/mm²

82							
146	111	91					
229	174	143	114				
329	251	206	164				
448	341	280	223	183			
585	446	366	292	239	156		
		571	456	373	243	166	
			656	537	351	239	
				731	478	325	
					624	424	335
					975	663	523
						955	753

For Stainless Steel: Use next bigger size of bottom tool

Empirical rule:
For air bending the inner radius Ri is approx. 16% of the die opening V. The values Ri and B are valid for 90° bends.



Calculation basics 3-point-bending

Calculation of the hydrocushion - force

Calculation of the cushion-force for 1 top tool section of a length of 100 mm:

$$F_K = \frac{A_{1ST} (\text{cm}^2) \times P_K (\text{bar})}{100}$$

F_K = capacity of the cushion


A_{1ST} = subjected surface of the hydrocushion ($B \times L$)

P_K = hydrocushion - force

Sample calculation:

Capacity of cushion F_K for 1 top tool section of 100mm length by a cushion pressure of 50 bar.


$$F_K = \frac{B (\text{cm}) \times L (\text{cm}) \times P_K (\text{bar})}{100}$$



Maximum capacity of the hydrocushion 1000 kN/m (100 t/m)

Calculation basics 3-point-bending

Calculation of the hydrocushion - force




Maximum capacity of the hydrocushion 1000 kN/m (100 t/m)

Calculation basics 3-point-bending

Working space on the Hämmerle 3-point-bending-machine

166



Calculation basics 3-point-bending

Working space on the Hämmerle 3-point-bending-machine

167

SH	DL	Typ	Typ	PH	FS (M = 86)	BH	Operation
Stroke	Open height	Punch holder	Punch	Top tool height	Free space	max. box height	Hemming
265	780	21.002.00	11.001.00	245	204	110	ja
		21.004.00	11.003.00	245	204	110	nein
		21.004.00	22.006.00 11.010.00	367	82	196	nein
		21.005.00	11.007.00	320	129	163	nein
400	915	21.002.00	11.001.00	245	339	110	ja
		21.002.00	11.003.00	295	289	145	nein
		21.003.00	22.006.00 11.010.01	330	254	170	nein
		21.004.00	11.003.00	245	339	110	nein
		21.004.00	12.015.00	245	339	110	nein
		21.004.00	22.006.00 11.010.01	367	217	196	nein
		21.005.00	11.001.00	350	234	184	ja
		21.005.00	11.003.00	400	184	219	nein
		21.005.00	11.007.00	320	264	163	nein
		21.005.00	12.015.00	400	184	219	nein
		21.010.00 *	11.001.00	400	184	219	ja
		21.010.00 *	12.015.00	450	134	255	nein

* The top tool combinations are limited for sheet thickness up to max. of 3mm.

Formula

For calculation of the max. box height:

$$BH \text{ (mm)} = \frac{[PH \text{ (mm)} - 90]}{\sqrt{2}}$$


For calculation of the top tool height:

$$PH \text{ (mm)} = BH \text{ (mm)} \times \sqrt{2} + 90$$

Description upper tools

Hydraulic fast clamping system of the upper tools.


Hydraulic fast clamping system of the upper tools
(Standard Hämmerle 3P)



1000 kN/m



vertical insertion



head supported



hydraulic




tools are reversible

Automatic centering of the tool during clamping ensures quick set up times. The segmented tool system offers total flexibility with regard to different bending lengths.

Description upper tools


Upper tooling

1 set standard top tools




A top tool always consists of the punch and the punch holder.
The punch holder is available in a length of L = 100mm or 200mm.

Upper tools - intermediate pieces - Intermediate pieces with horn



1 set of intermediate top tool sections without horn consists of 10 pieces.




1 set of intermediate top tool sections with horn consists of 8 pieces.

Description upper tools

Standard holder and 3 point upper tool combination

punch holder	21.002.00	21.004.00	21.005.00
punch	11.001.00	12.015.00	11.001.00




The max. permitted load of the tool combination is equal to the max. permitted load of the punch.

Description upper tools

Standard holder and 3 point upper tool combination

punch holder	21.005.00	21.010.00 *	21.010.00 *
punch	12.015.00	11.001.00	12.015.00




Top tool combinations with the punch holders 21.010.00 are limited for steel thickness up to max. 3mm.

11.001.00

[R] Radius (mm)	1
Nose angle	30°
[H] Height (mm)	90
[B] Width (mm)	6

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 0.397 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11001

Standard length	Part number
100 mm	B8-11.001.01.01
50 / 55 / 60 mm	B8-11.001.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.001.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.001.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.001.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.001.04.01 / 02 / 03 / 04 / 05

11.001.00 + 21.002.00


$F = 1000 \text{ kN/m}$
 $R = 1 \text{ mm}$
 $H = 90 \text{ mm}$

11.028.00

[R] Radius (mm)	1
Nose angle	28°
[H] Height (mm)	90
[B] Width (mm)	6

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 0.397 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11028

Standard length	Part number
100 mm	B8-11.028.01.01
50 / 55 / 60 mm	B8-11.028.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.028.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.028.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.028.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.028.04.01 / 02 / 03 / 04 / 05

11.028.00 + 21.002.00

F = 1000 kN/m
R = 1 mm
H = 90 mm

Standard length	Part number
100 mm	B8-10.0001.1
200 mm	B8-10.0002.1
segmented 50 - 95	B8-10.0003.1
Horn set 50 - 115	B8-10.0014.1

11.003.00

[R] Radius (mm)	1
Nose angle	30
[H] Height (mm)	140
[B] Width (mm)	6

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 0.627 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No.** BH11003

Standard length	Part number
100 mm	B8-11.003.01.01
50 / 55 / 60 mm	B8-11.003.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.003.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.003.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.003.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.003.04.01 / 02 / 03 / 04 / 05


11.003.00 + 21.002.00

11.003.00 + 21.002.00	
	$F = 1000 \text{ kN/m}$
	$R = 1 \text{ mm}$
	$H = 140 \text{ mm}$
Standard length	Part number
100 mm	B8-10.1717
200 mm	B8-10.1721
segmented 50 - 95	B8-10.1347
Horn set 50 - 115	B8-10.1348

11.006.00

[R] Radius (mm)	2
Nose angle	30
[H] Height (mm)	90
[B] Width (mm)	8

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 0.448 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11006

11.006.00 + 21.002.00

$F = 1000 \text{ kN/m}$
 $R = 2 \text{ mm}$
 $H = 90 \text{ mm}$

Standard length	Part number
100 mm	B8-11.006.01.01
50 / 55 / 60 mm	B8-11.006.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.006.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.006.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.006.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.006.04.01 / 02 / 03 / 04 / 05


Standard length	Part number
100 mm	B8-10.0098
200 mm	B8-10.0099
segmented 50 - 95	B8-10.0100
Horn set 50 - 115	B8-10.0111

11.008.00

[R] Radius (mm)	1
Nose angle	30
[H] Height (mm)	90
[B] Width (mm)	8

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 0.438 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stocki / 24 h
- BOS No. BH11008

Standard length	Part number
100 mm	B8-11.008.01.01
50 / 55 / 60 mm	B8-11.008.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.008.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.008.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.008.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.008.04.01 / 02 / 03 / 04 / 05

11.008.00 + 21.002.00

F = 1000 kN/m
R = 1 mm
H = 90 mm


Standard length	Part number
100 mm	B8-10.0160
200 mm	B8-10.0161
segmented 50 - 95	B8-10.0162
Horn set 50 - 115	B8-10.0173

11.010.00

[R] Radius (mm)	1
Nose angle	30
[H] Height (mm)	40
[B] Width (mm)	6

- 42 CrMo4
- 58 - 62 HRC
- Fmax = 600 kN/m
- Operator side
- Head supported
- 0.165 kg/100 mm
- Hämmerle 3P
- 195.0 mm
- Ex stock / 24 h
- BOS No. BH11010

Standard length	Part number
100 mm	B8-11.010.01.01
50 / 55 / 60 mm	B8-11.010.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.010.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.010.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.010.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.010.04.01 / 02 / 03 / 04 / 05

11.010.00 + 22.006.00 + 21.004.00

F = 600 kN/m
R = 1 mm
H = 40 mm


Standard length	Part number
100 mm	B8-10.1162
segmented 50 - 95	B8-10.1301

11.033.10

[R] Radius (mm)	3
Nose angle	-
[H] Height (mm)	90
[B] Width (mm)	8

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 0.451 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11033

Standard length	Part number
100 mm	B8-11.033.11.01
50 / 55 / 60 mm	B8-11.033.12.01 / 02 / 03
65 / 70 / 75 mm	B8-11.033.12.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.033.12.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.033.15.01 / 14.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.033.14.01 / 02 / 03 / 04 / 05

11.033.10 + 21.002.00

$F = 1000 \text{ kN/m}$
 $R = 3 \text{ mm}$
 $H = 90 \text{ mm}$


Standard length	Part number
100 mm	B8-10.0424
200 mm	B8-10.0425
segmented 50 - 95	B8-10.0426
Horn set 50 - 115	B8-10.0437

11.034.00

[R] Radius (mm)	4
Nose angle	30
[H] Height (mm)	90
[B] Width (mm)	8

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 0.620 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11034

Standard length	Part number
100 mm	B8-11.034.01.01
50 / 55 / 60 mm	B8-11.034.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.034.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.034.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.034.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.034.04.01 / 02 / 03 / 04 / 05

11.034.00 + 21.002.00

F = 1000 kN/m
R = 4 mm
H = 90 mm


Standard length	Part number
100 mm	B8-10.0445
200 mm	B8-10.0446
segmented 50 - 95	B8-10.0447
Horn set 50 - 115	B8-10.1926

11.035.00

[R] Radius (mm)	5
Nose angle	-
[H] Height (mm)	90
[B] Width (mm)	8

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 0.628 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11035

Standard length	Part number
100 mm	B8-11.035.01.01
50 / 55 / 60 mm	B8-11.035.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.035.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.035.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.035.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.035.04.01 / 02 / 03 / 04 / 05

11.035.00 + 21.002.00

F = 1000 kN/m
R = 5 mm
H = 90 mm


Standard length	Part number
100 mm	B8-10.0458
200 mm	B8-10.0459
segmented 50 - 95	B8-10.0460
Horn set 50 - 115	B8-10.0471

11.036.00

[R] Radius (mm)	6
Nose angle	-
[H] Height (mm)	90
[B] Width (mm)	9

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 0.733 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11036

Standard length	Part number
100 mm	B8-11.036.01.01
50 / 55 / 60 mm	B8-11.036.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.036.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.036.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-11.036.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-11.036.04.01 / 02 / 03 / 04 / 05

11.036.00 + 21.002.00

F = 1000 kN/m
R = 6 mm
H = 90 mm

Standard length	Part number
100 mm	B8-10.1240
200 mm	B8-10.1335
segmented 50 - 95	B8-10.1912
Horn set 50 - 115	B8-10.1927

12.014.00

[R] Radius (mm)	1
Nose angle	85
[H] Height (mm)	140
[B] Width (mm)	59

42 CrMo 4

58 - 62 HRC

$F_{max} = 975 \text{ kN/m}$

Operator side

Head supported


3.358 kg/100 mm

Hämmerle 3P

110.0 mm

Ex stock / 24 h

BOS No. BH12014

12.014.00 + 21.004.00

$F = 975 \text{ kN/m}$
 $R = 1 \text{ mm}$
 $H = 140 \text{ mm}$

Standard length	Part number
100 mm	B8-12.014.01.01
50 / 55 / 60 mm	B8-12.014.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.014.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.014.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.014.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.014.04.01 / 02 / 03 / 04 / 05

Standard length	Part number
100 mm	B8-10.0243
200 mm	B8-10.0244
segmented 50 - 95	B8-10.0245
Horn set 50 - 115	B8-10.0256

12.015.00




[R] Radius (mm)	1
Nose angle	85
[H] Height (mm)	140
[B] Width (mm)	45

- 42 CrMo 4
- 58 - 62 HRC
- F_{max} = 975 kN/m
- Operator side
- Head supported
- 2.620 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH12015

Standard length	Part number
100 mm	B8-12.015.01.01
50 / 55 / 60 mm	B8-12.015.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.015.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.015.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.015.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.015.04.01 / 02 / 03 / 04 / 05

12.015.00 + 21.004.00



F = 975 kN/m
R = 1 mm
H = 140 mm


Standard length	Part number
100 mm	B8-10.0285
200 mm	B8-10.0286
segmented 50 - 95	B8-10.0287
Horn set 50 - 115	B8-10.0298

12.017.00

[R] Radius (mm)	1
Nose angle	55
[H] Height (mm)	190
[B] Width (mm)	34

- 42 CrMo 4
- 58 - 62 HRC
- F_{max} = 750 kN/m
- Operator side
- Head supported
- 2.755 kg/100 mm
- Hämmerle 3P
- 145.0 mm
- Ex stock / 24 h
- BOS No. BH12017

Standard length	Part number
100 mm	B8-12.017.01.01
50 / 55 / 60 mm	B8-12.017.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.017.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.017.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.017.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.017.04.01 / 02 / 03 / 04 / 05

12.017.00 + 21.004.00

F = 750 kN/m
R = 1 mm
H = 190 mm

12.025.00

[R] Radius (mm)	1
Nose angle	85
[H] Height (mm)	140
[B] Width (mm)	22

42 CrMo 4

58 - 62 HRC

$F_{max} = 250 \text{ kN/m}$

Operator side

Head supported


1.354 kg/100 mm

Hämmerle 3P

110.0 mm

Ex stock / 24 h

BOS No. BH12025

12.025.00 + 21.004.00

$F = 250 \text{ kN/m}$
 $R = 1 \text{ mm}$
 $H = 140 \text{ mm}$

Standard length	Part number
100 mm	B8-12.025.01.01
50 / 55 / 60 mm	B8-12.025.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.025.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.025.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.025.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.025.04.01 / 02 / 03 / 04 / 05


Standard length	Part number
100 mm	B8-10.1506
200 mm	B8-10.1507
segmented 50 - 95	B8-10.1929
Horn set 50 - 115	B8-10.1930

12.052.00

[R] Radius (mm)	2
Nose angle	85
[H] Height (mm)	140
[B] Width (mm)	45

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 975 kN/m
- Operator side
- Head supported
- 2.622 kg/100 mm
- Häammerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH12052

Standard length	Part number
100 mm	B8-12.052.01.01
50 / 55 / 60 mm	B8-12.052.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.052.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.052.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.052.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.052.04.01 / 02 / 03 / 04 / 05

12.052.00 + 21.004.00

F = 975 kN/m
R = 2 mm
H = 140 mm

Standard length	Part number
100 mm	B8-10.0479
200 mm	B8-10.0480
segmented 50 - 95	B8-10.0481
Horn set 50 - 115	B8-10.0492

12.053.00

[R] Radius (mm)	3
Nose angle	85
[H] Height (mm)	140
[B] Width (mm)	45

42 CrMo 4

58 - 62 HRC

Fmax = 975 kN/m

Operator side

Head supported


2.644 kg/100 mm

Hämmerle 3P

110.0 mm

Ex stock / 24 h

BOS No. BH12053

12.053.00 + 21.004.00

F = 975 kN/m
R = 3 mm
H = 140 mm

Standard length	Part number
100 mm	B8-12.053.01.01
50 / 55 / 60 mm	B8-12.053.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.053.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.053.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.053.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.053.04.01 / 02 / 03 / 04 / 05


Standard length	Part number
100 mm	B8-10.0500
200 mm	B8-10.0501
segmented 50 - 95	B8-10.0502
Horn set 50 - 115	B8-10.0513

12.065.00

[R] Radius (mm)	1
Nose angle	50
[H] Height (mm)	140
[B] Width (mm)	16

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 1.360 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH12065

Standard length	Part number
100 mm	B8-12.065.01.01
50 / 55 / 60 mm	B8-12.065.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.065.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.065.02.07 / 08 / 09 / 10
Horns 75 l / 80 l	B8-12.065.05.01 / 04.06
75 r / 85 r / 95 r / 105 r / 115 r	B8-12.065.04.01 / 02 / 03 / 04 / 05

12.065.00 + 21.004.00

$F = 1000 \text{ kN/m}$
 $R = 1 \text{ mm}$
 $H = 140 \text{ mm}$

Standard length	Part number
100 mm	B8-10.0521
200 mm	B8-10.0522
segmented 50 - 95	B8-10.0523
Horn set 50 - 115	B8-10.0534

14.021.00



[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	140
[B] Width (mm)	10

42 CrMo 4

58 - 62 HRC

F_{max} = 1000 kN/m

Operator side

Head supported


1.085 kg/100 mm

Hämmerle 3P

Ex stock / 24 h

BOS No. BH14021

14.021.00 + 21.004.00



F = 1000 kN/m
R = ---
H = 140 mm

Standard length	Part number
100 mm	B8-14.021.01.01
50 / 55 / 60 mm	B8-14.021.02.01 / 02 / 03
65 / 70 / 75 mm	B8-14.021.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-14.021.02.07 / 08 / 09 / 10


Standard length	Part number
100 mm	B8-10.0369
200 mm	B8-10.0370
segmented 50 - 95	B8-10.0371

22.006.00

[R] Radius (mm)	-
Nose angle	-
[H] Height (mm)	222
[B] Width (mm)	99

- 42 CrMo 4
-
- Fmax = 600 kN/m
- Operator side
- Head supported
- 10.300 kg/100 mm
- Hämmerle 3P
- variable
- Ex stock / 24 h
- BOS No. BH22006

Standard length	Part number
100 mm	B8-22.006.01.01
50 / 55 / 60 mm	B8-22.006.02.01 / 02 / 03
65 / 70 / 75 mm	B8-22.006.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-22.006.02.07 / 08 / 09 / 10

22.006.00 + 21.004.00

F = 600 kN/m
R = ---
H = 222

Radius punch holder 22.013.00

[R] Radius (mm) 6-12.5

Nose angle -

[H] Height (mm) 120

[B] Width (mm) 37

42 CrMo 4

F_{max} = 1000 kN/m

Operator side

Head supported

2.820 kg/100 mm

Hämmerle 3P


variable

Ex stock / 24 h

BOS No. BH22013

22.013.00

F = 1000 kN/m
R = ---
H = 120



Radius punch holder 22.014.00

[R] Radius (mm) 8-20

Nose angle -

[H] Height (mm) 120

[B] Width (mm) 37

42 CrMo 4

F_{max} = 1000 kN/m

Operator side

Head supported

3.050 kg/100 mm

Hämmerle 3P


variable

Ex stock / 24 h

BOS No. BH22014

22.014.00

F = 1000 kN/m
R = ----
H = 120 mm



Standard length	Part number
100 mm	B8-22.014.01.01
50 / 55 / 60 mm	B8-22.014.02.01 / 02 / 03
65 / 70 / 75 mm	B8-22.014.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-22.014.02.07 / 08 / 09 / 10

Radius punch holder 22.015.00



[R] Radius (mm) 18-45

Nose angle -

[H] Height (mm) 112

[B] Width (mm) 40.5

42 CrMo 4

F_{max} = 1000 kN/m

Operator side

Head supported

3.280 kg/100 mm

Hämmerle 3P


variable

Ex stock / 24 h

BOS No. BH22015

22.015.00

F = 1000 kN/m
R = ---
H = 112 mm




Coining upper tool 11.005.00

[R] Radius (mm)	-
Nose angle	90
[H] Height (mm)	90
[B] Width (mm)	6

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 1000 \text{ kN/m}$
- Operator side
- Head supported
- 0.42 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH11005

Standard length	Part number
100 mm	B8-11.005.01.01
50 / 55 / 60 mm	B8-11.005.02.01 / 02 / 03
65 / 70 / 75 mm	B8-11.005.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.005.02.07 / 08 / 09 / 10

11.005.00 + 21.002.00

$F = 1000 \text{ kN/m}$
 $R = ---$
 $H = 90 \text{ mm}$


Standard length	Part number
100 mm	B8-10.0077
200 mm	B8-10.0078
segmented 50 - 95	B8-10.0079

Coining upper tool 11.009.10

[R] Radius (mm)	-
Nose angle	90
[H] Height (mm)	140
[B] Width (mm)	12

- 42 CrMo 4
- 58 - 62 HRC
- Fmax = 1000 kN/m
- Operator side
- Head supported
- 1.20 kg/100 mm
- Hämmerle 3P
- 150.0 mm
- Ex stock / 24 h
- BOS No. BH11009

Standard length	Part number
100 mm	B8-11.009.11.01
50 / 55 / 60 mm	B8-11.009.12.01 / 02 / 03
65 / 70 / 75 mm	B8-11.009.12.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-11.009.12.07 / 08 / 09 / 10

11.009.10 + 21.002.00

F = 1000 kN/m
R = ---
H = 140 mm


Standard length	Part number
100 mm	B8-10.1511
200 mm	B8-10.1931
segmented 50 - 95	B8-10.1512

Coining upper tool 12.019.00

[R] Radius (mm)	1
Nose angle	90
[H] Height (mm)	140
[B] Width (mm)	45

- 42 CrMo 4
- 58 - 62 HRC
- $F_{max} = 975 \text{ kN/m}$
- Operator side
- Head supported
- 2.60 kg/100 mm
- Hämmerle 3P
- 110.0 mm
- Ex stock / 24 h
- BOS No. BH12019



Standard length	Part number
100 mm	B8-12.019.01.01
50 / 55 / 60 mm	B8-12.019.02.01 / 02 / 03
65 / 70 / 75 mm	B8-12.019.02.04 / 05 / 06
80 / 85 / 90 / 95 mm	B8-12.019.02.07 / 08 / 09 / 10

12.019.00 + 21.004.00

$F = 975 \text{ kN/m}$
 $R = 1 \text{ mm}$
 $H = 140 \text{ mm}$

Standard length	Part number
100 mm	B8-10.0327
200 mm	B8-10.0328
segmented 50 - 95	B8-10.0329

Bottom tools 3 - point - bending



Bottom tools 3-point-bending


Recommendation starterkit Hämmerle 3P

Bend length	Part number	Description	Piece	Unit
2100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	17	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	3	pieces
3100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	27	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	5	pieces
4100 mm	B8-10.0001.1	Punch + holder 11.028.00/21.002.00/100	37	pieces
	B8-10.0002.1	Punch + holder 11.028.00/21.002.00/200	2	pieces
	B8-10.0646	Die kpl.GS/Fld. 31.012.00/WL100	6	pieces
	B8-10.0647	Die kpl.GS/Fld. 31.012.00/WL500	7	pieces

Description bottom tools

Hydraulic fast clamping system of the bottom tools

Hydraulic fast clamping system of the bottom tools
(Standard Hämmerle 3P)



60-62 HRC




1000 kN/m



hydraulic

Shortest setup times
are guaranteed by
the hydraulic quick
clamping system of
the lower tools.





Description bottom tools

Bottom tools segmentation

Bottom tool intermediate pieces

For bottom tools up to 60mm V-opening intermediate pieces are also available.
1 set consists of 10 intermediate pieces.





Description bottom tools

226


Standard pieces

Bottom tools

Indications with regards to material thickness and angle range refer to mild steel plates with a tensile strength of $R_m = 450 \text{ N/mm}^2$.



Standard bottom tool piece L = 100 mm with holding rail L = 100 mm.




5 standard bottom tools with holding rail L = 500mm.

A bottom tool always consists of the basic bottom tool body, a holding rail and the bottom tool pins.

Notes

227



31.005.00 H-S

[R] Radius (mm)	0.6
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	14
Material thickness (mm)	0.5 - 1

Standard length	Part number
100 mm	B8-10.1250
500 mm	B8-10.1255
segmented 50 - 95	B8-10.1256



42 CrMo 4



58 - 62 HRC



Fmax = 250 kN/m



1.70 Kg/100 mm




Hämmerle 3P



Ex stock / 24 h



005.00-01

31.005.00 H-FLD

[R] Radius (mm)	0.6
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	14
Material thickness (mm)	0.5 - 1



42 CrMo 4



58 - 62 HRC



Fmax = 250 kN/m



1.70 kg/100 mm



Hämmerle 3P




Ex stock / 24 h



005.00-08

31.006.00 H-S

230



[R] Radius (mm)	2
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	14
Material thickness (mm)	0.5 - 1.25

Standard length	Part number
100 mm	B8-10.1535
500 mm	B8-10.1536
segmented 50 - 95	B8-10.1537



42 CrMo 4



58 - 62 HRC



Fmax = 350 kN/m



1.71 Kg/100 mm



Hämmerle 3P



Ex stock / 24 h




BOS No.

006.00-01

31.006.00 H-FLD

231



[R] Radius (mm)	2
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	14

Standard length	Part number
100 mm	B8-10.1420
500 mm	B8-10.1421
segmented 50 - 95	B8-10.1422



42 CrMo 4



56 - 62 HRC



Fmax = 350 kN/m




1.71 kg/100 mm



Hämmerle 3P



Ex stock / 24 h




BOS No.

006.00-08

31.007.00 H-S

232



[R] Radius (mm)	1
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	19
Material thickness (mm)	0.5 - 1.5

Standard length	Part number
100 mm	B8-10.0542
500 mm	B8-10.0543
segmented 50 - 95	B8-10.0544



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



1.87 Kg/100 mm



Hämmerle 3P




Ex stock / 24 h



007.00-01

31.007.00 H-FLD

233



[R] Radius (mm)	1
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	19
Material thickness (mm)	0.5 - 1.5



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



1.87 kg/100 mm




Hämmerle 3P



Ex stock / 24 h





007.00-02

31.007.20 H-S


[R] Radius (mm)	2.5
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	19
Material thickness (mm)	0.5 - 1.5


Standard length	Part number
100 mm	B8-10.0568
500 mm	B8-10.0569
segmented 50 - 95	B8-10.0570

**31.007.20 H-FLD**

[R] Radius (mm)	2.5
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	19
Material thickness (mm)	0.5 - 1.5

Standard length	Part number
100 mm	B8-10.0581
500 mm	B8-10.0582
segmented 50 - 95	B8-10.0583



31.010.20 H-S

[R] Radius (mm)	1
V - Angle	85-180
[H] Height (mm)	86
[B] Width (mm)	19
Material thickness (mm)	0.7 - 2.5

Standard length	Part number
100 mm	B8-10.0620
500 mm	B8-10.0621
segmented 50 - 95	B8-10.0622



42 CrMo 4



58 - 62 HRC



Fmax = 550 kN/m



1.70 Kg/100 mm




Hämmerle 3P



Ex stock / 24 h



010.20-01

31.012.00 H-S

[R] Radius (mm)	1.5
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	28

Standard length	Part number
100 mm	B8-10.0633
500 mm	B8-10.0634
segmented 50 - 95	B8-10.0635



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



2.39 kg/100 mm




Hämmerle 3P



Ex stock / 24 h





012.00-01

31.012.00 H-FLD


[R] Radius (mm)	1.5
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	0.7 - 3.0

Standard length	Part number
100 mm	B8-10.0646
500 mm	B8-10.0647
segmented 50 - 95	B8-10.0648


**31.013.00 H-S**

[R] Radius (mm)	3
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	0.7 - 3.0

Standard length	Part number
100 mm	B8-10.0659
500 mm	B8-10.0660
segmented 50 - 95	B8-10.0661



31.013.00 H-FLD



[R] Radius (mm)	3
V - Angle	30-180
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	0.7 - 3.0

Standard length	Part number
100 mm	B8-10.0672
500 mm	B8-10.0673
segmented 50 - 95	B8-10.0674



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



2.40 Kg/100 mm



Hämmerle 3P




Ex stock / 24 h



013.00-03

31.016.00 H-S



[R] Radius (mm)	2
V - Angle	45-150
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	1.5 - 4.0

Standard length	Part number
100 mm	B8-10.0685
500 mm	B8-10.0686
segmented 50 - 95	B8-10.0687



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



2.14 kg/100 mm




Hämmerle 3P



Ex stock / 24 h



016.00-01

31.016.10 H-S

[R] Radius (mm)	3.5
V - Angle	45-150
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	1.5 - 4.0

Standard length	Part number
100 mm	B8-10.0698
500 mm	B8-10.0699
segmented 50 - 95	B8-10.0700



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m




2.18 Kg/100 mm




Hämmerle 3P



Ex stock / 24 h



016.10-01

31.021.00 H-S

[R] Radius (mm)	3.5
V - Angle	60-160
[H] Height (mm)	86
[B] Width (mm)	28

Standard length	Part number
100 mm	B8-10.0724
500 mm	B8-10.0725
segmented 50 - 95	B8-10.0726



42 CrMo 4



58 - 62 HRC



Fmax = 500 kN/m



2.14 kg/100 mm




Hämmerle 3P



Ex stock / 24 h



021.00-01

31.024.00 H-S

[R] Radius (mm)	2
V - Angle	70-140
[H] Height (mm)	86
[B] Width (mm)	34
Material thickness (mm)	2.0 - 5.0

Standard length	Part number
100 mm	B8-10.0750
500 mm	B8-10.0751
segmented 50 - 95	B8-10.0752



42 CrMo 4



58 - 62 HRC



Fmax = 750 kN/m



2.44 Kg/100 mm




Hämmerle 3P



Ex stock / 24 h



024.00-04

31.032.10 H-S

[R] Radius (mm)	2
V - Angle	85-160
[H] Height (mm)	86
[B] Width (mm)	40

Standard length	Part number
100 mm	B8-10.0763
500 mm	B8-10.0764
segmented 50 - 95	B8-10.0765



42 CrMo 4



58 - 62 HRC



Fmax = 1200 kN/m



2.80 kg/100 mm




Hämmerle 3P



Ex stock / 24 h



032.00-06

31.040.10 H-S

[R] Radius (mm)	4
V - Angle	70-180
[H] Height (mm)	86
[B] Width (mm)	48
Material thickness (mm)	3.5 - 7.0

Standard length	Part number
100 mm	B8-10.0776
500 mm	B8-10.0777
segmented 50 - 95	B8-10.0778



42 CrMo 4



58 - 62 HRC



Fmax = 750 kN/m



2.96 Kg/100 mm




Hämmerle 3P



Ex stock / 24 h



040.10-05

31.060.00 H-S

[R] Radius (mm)	8
V - Angle	70-180
[H] Height (mm)	86
[B] Width (mm)	75
Material thickness (mm)	4.0 - 10.0

Standard length	Part number
100 mm	B8-10.0802
500 mm	B8-10.0803
segmented 50 - 95	B8-10.0804



42 CrMo 4



58 - 62 HRC



Fmax = 1500 kN/m



4.06 kg/100 mm



Hämmerle 3P




Ex stock / 24 h



060.00-05

31.090.00 H-S

248



[R] Radius (mm)	8
V - Angle	70-180
[H] Height (mm)	120
[B] Width (mm)	122
Material thickness (mm)	5.0 - 12.0

Standard length	Part number
100 mm	B8-10.0841
200 mm	B8-10.0843



42 CrMo 4



58 - 62 HRC



Fmax = 1500 kN/m



8.80 Kg/100 mm



Hämmerle 3P




Ex stock / 24 h



090.00-07

31.110.00 H-S

249



[R] Radius (mm)	8
V - Angle	75-180
[H] Height (mm)	120
[B] Width (mm)	144
Material thickness (mm)	8.0 - 15.0

Standard length	Part number
100 mm	B8-10.0852
200 mm	B8-10.0854



42 CrMo 4



58 - 62 HRC



Fmax = 1500 kN/m



9.48 kg/100 mm




Hämmerle 3P



Ex stock / 24 h





110.00-07

Coining bottom tool 41.005.00


[R] Radius (mm)	1
V - Angle	90
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	0.5 - 1.0


Standard length	Part number
100 mm	B8-10.0855
500 mm	B8-10.0856
segmented 50 - 95	

**Coining bottom tool 41.007.00**

[R] Radius (mm)	1
V - Angle	90
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	0.4 - 1.5



Standard length	Part number
100 mm	B8-10.0868
500 mm	B8-10.0869
segmented 50 - 95	B8-10.0870




Coining bottom tool 41.010.00


[R] Radius (mm)	2
V - Angle	90
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	1.0 - 2.0

Standard length	Part number
100 mm	B8-10.0881
500 mm	B8-10.0882
segmented 50 - 95	B8-10.0883

**Coining bottom tool 41.012.00**


[R] Radius (mm)	2
V - Angle	90
[H] Height (mm)	86
[B] Width (mm)	28
Material thickness (mm)	1.0 - 2.5





Bottom tool pin**61.200.21**

Part number	Size (mm)	Weight (Kg)
.01	20 x 87	0,06
.02	15 x 87	0,05

61.200.21.01




61.200.21.02



**Bottom tool pin****61.200.23**

Part number	Size (mm)	Weight (Kg)
.01	20 x 85	0,06
.02	15 x 85	0,05

61.200.23.01




61.200.23.02



**61.200.22**

Part number	Size (mm)	Weight (Kg)
.01	20 x 83	0,06
.02	15 x 83	0,05

61.200.22.01




61.200.22.02


**61.200.24**


Part number	Size (mm)	Weight (Kg)
.01	20 x 87	0,06
.02	15 x 87	0,05

61.200.24.01




61.200.24.02





Bottom tool pin**61.200.25**

Part number	Size (mm)	Weight (Kg)
.01	20 x 87	0,06
.02	15 x 87	0,05

61.200.25.01




61.200.25.02


**61.200.26**

Part number	Size (mm)	Weight (Kg)
.01	20 x 87	0,06
.02	15 x 87	0,05

61.200.26.01




61.200.26.02


**Bottom tool pin****61.200.27**

Part number	Size (mm)	Weight (Kg)
.01	20 x 87	0,02
.02	15 x 87	0,01

61.200.27.01




61.200.27.02

**61.200.28**

Part number	Size (mm)	Weight (Kg)
.01	20 x 85	0,06
.02	15 x 85	0,05


61.200.28.01



61.200.28.02




Bottom tool pin


**61.200.29**

Part number	Size (mm)	Weight (Kg)
.01	20 x 62	0,06
.02	15 x 62	0,05


61.200.29.01



61.200.29.02




Bottom tool pin


**61.200.31**

Part number	Size (mm)	Weight (Kg)
.01	20 x 77	0,06
.02	15 x 77	0,05

61.200.31.01



61.200.31.02



Insert rails

Who will need insert rails?

To provide maximum flexibility in the range of angle that can be formed using lower tools from 31.040.10 (V40) and larger, insert rails are available.


Details of the various insert rails available are provided on the following pages.

(All insert rails are manufactured from CK45 steel and have a hardness of 58 - 60 HRC.)



Insert rails

Insert rail 61.500.01




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.01.01	100	20 x 10	0,16
B8-61.500.01.02	50	20 x 10	0,08
B8-61.500.01.03	55	20 x 10	0,088
B8-61.500.01.04	60	20 x 10	0,096
B8-61.500.01.05	65	20 x 10	0,104
B8-61.500.01.06	70	20 x 10	0,112
B8-61.500.01.07	75	20 x 10	0,120
B8-61.500.01.08	80	20 x 10	0,128
B8-61.500.01.09	85	20 x 10	0,136
B8-61.500.01.10	90	20 x 10	0,144
B8-61.500.01.11	95	20 x 10	0,152
B8-61.500.01.12	500	20 x 10	0,8

Insert rails

262

Insert rail 61.500.04




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.04.01	100	30 x 11	0,26
B8-61.500.04.02	50	30 x 11	0,13
B8-61.500.04.03	55	30 x 11	0,143
B8-61.500.04.04	60	30 x 11	0,156
B8-61.500.04.05	65	30 x 11	0,169
B8-61.500.04.06	70	30 x 11	0,182
B8-61.500.04.07	75	30 x 11	0,195
B8-61.500.04.08	80	30 x 11	0,208
B8-61.500.04.09	85	30 x 11	0,221
B8-61.500.04.10	90	30 x 11	0,234
B8-61.500.04.11	95	30 x 11	0,247
B8-61.500.04.12	500	30 x 11	1,3

Insert rails

263

Insert rail 61.500.05




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.05.01	100	20 x 10	0,5
B8-61.500.05.02	50	20 x 10	0,25
B8-61.500.05.03	55	20 x 10	0,275
B8-61.500.05.04	60	20 x 10	0,3
B8-61.500.05.05	65	20 x 10	0,325
B8-61.500.05.06	70	20 x 10	0,35
B8-61.500.05.07	75	20 x 10	0,375
B8-61.500.05.08	80	20 x 10	0,4
B8-61.500.05.09	85	20 x 10	0,425
B8-61.500.05.10	90	20 x 10	0,45
B8-61.500.05.11	95	20 x 10	0,475
B8-61.500.05.12	500	20 x 10	2,5

Insert rails

264

Insert rail 61.500.04




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.04.01	100	30 x 11	0,26
B8-61.500.04.02	50	30 x 11	0,13
B8-61.500.04.03	55	30 x 11	0,143
B8-61.500.04.04	60	30 x 11	0,156
B8-61.500.04.05	65	30 x 11	0,169
B8-61.500.04.06	70	30 x 11	0,182
B8-61.500.04.07	75	30 x 11	0,195
B8-61.500.04.08	80	30 x 11	0,208
B8-61.500.04.09	85	30 x 11	0,221
B8-61.500.04.10	90	30 x 11	0,234
B8-61.500.04.11	95	30 x 11	0,247
B8-61.500.04.12	500	30 x 11	1,3

Insert rails

265

Insert rail 61.500.05




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.05.01	100	20 x 10	0,5
B8-61.500.05.02	50	20 x 10	0,25
B8-61.500.05.03	55	20 x 10	0,275
B8-61.500.05.04	60	20 x 10	0,3
B8-61.500.05.05	65	20 x 10	0,325
B8-61.500.05.06	70	20 x 10	0,35
B8-61.500.05.07	75	20 x 10	0,375
B8-61.500.05.08	80	20 x 10	0,4
B8-61.500.05.09	85	20 x 10	0,425
B8-61.500.05.10	90	20 x 10	0,45
B8-61.500.05.11	95	20 x 10	0,475
B8-61.500.05.12	500	20 x 10	2,5

Insert rails

266

Insert rail 61.500.06




Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.06.01	100	30 x 33	0,78
B8-61.500.06.02	50	30 x 33	0,39
B8-61.500.06.03	55	30 x 33	0,429
B8-61.500.06.04	60	30 x 33	0,468
B8-61.500.06.05	65	30 x 33	0,507
B8-61.500.06.06	70	30 x 33	0,546
B8-61.500.06.07	75	30 x 33	0,585
B8-61.500.06.08	80	30 x 33	0,624
B8-61.500.06.09	85	30 x 33	0,663
B8-61.500.06.10	90	30 x 33	0,702
B8-61.500.06.11	95	30 x 33	0,741
B8-61.500.06.12	500	30 x 33	3,9

Insert rails

267

Insert rail 61.500.07



Part number	Length (mm)	Size (mm)	Weight (kg)
B8-61.500.07.01	100	33 x 44	1,04
B8-61.500.07.02	50	33 x 44	0,52
B8-61.500.07.03	55	33 x 44	0,572
B8-61.500.07.04	60	33 x 44	0,624
B8-61.500.07.05	65	33 x 44	0,676
B8-61.500.07.06	70	33 x 44	0,728
B8-61.500.07.07	75	33 x 44	0,78
B8-61.500.07.08	80	33 x 44	0,832
B8-61.500.07.09	85	33 x 44	0,884
B8-61.500.07.10	90	33 x 44	0,936
B8-61.500.07.11	95	33 x 44	0,988
B8-61.500.07.12	500	33 x 44	5,2

Contacts

268

Bystronic do Brasil Ltda.
Rue Arapongas, 285
83.040-200
Sao José dos Pinhais Paraná
Brazil
Tel. +55 41 3398 2000
Fax +55 41 3398 1789

Bystronic Co., Ltd (Shanghai)
RiJing Road 88, WaiGaoQiao
FTZ PuDong, Shanghai
China 200131
Tel. +86 21 586 80 480
Fax +86 21 568 80 481

Bystronic Iberica, S.A.
Avenida Tenerife
2 Edificio Marpe I, 3a planta
ES-28700 San Sebastián de los
Reyes (Madrid)
España
Tel. +34 91 654 48 78
Fax +34 91 652 49 83

Bystronic Canada Ltd.
5730 Coopers Avenue #24
L4Z 2E9 Mississauga
Canada
Tel. +1 905 890 2999
Fax +1 905 890 2998

Bystronic DK
Ådalsvej 4
DK-4100 Ringsted
Danmark
Tel. +45 56 87 91 00
Fax +45 56 87 91 10

Bystronic France S.A.
Park Technopolis
3 Avenue du Canada
F-91940 Les Ulis
France
Tel. +33 1 69 41 99 84
Fax +33 1 69 41 99 51

Bystronic Czech Republic s.r.o.
Turanka 115/1222
PSC 627 00 Brno
Ceská Republika
Tel. +420 532 123 314
Fax +420 532 123 315

Bystronic Deutschland GmbH
Römerstraße 14
71296 Heimsheim
Deutschland
Tel. +49 7033 4699 0
Fax +49 7033 4699 222

Bystronic Laser India (Pvt) Ltd.
7 C, Tadiwala Road
Next to Hotel Panchratna
Pune 411 001
India
Tel. +91 20 67294800
Mobile +91 9922000542

Bystronic Italia SRL
Via del Lavoro 30
I-20183 Bovisio Masciago (MB)
Italia
Tel. +39 0362 59 93 1
Fax +39 0362 59 93 209

Bystronic Korea, B/D
1027-11 Hogye-Dong,
Dongan-Gu, Anyang-Si,
Gyeonggi-Do
Korea
Tel. +82 31 389 9800
Fax +82 31 389 9819

Bystronic Mexico S.A. de C.V.
Calle Canes 3250 Int.23,
Col. La Nogalera
44470 Guadalajara, Jalisco
Mexico
Tel. +52 33 3044 0505
Fax +52 33 1380 9979

Bystronic Benelux BV
Stek 8
NL-3371 KG Hardinxveld-
Giessendam
Nederland
Tel. +31 184 611 020
Fax +31 184 617 774

Bystronic Austria GmbH
Salzburger Straße 205
AT-4030 Linz
Österreich
Tel. +43 732 341 155
Fax +43 732 341 153

Bystronic Polska Sp. z o.o.
Al. Krakowska 38, Janki
PL-05-090 Raszyn
Polksa
Tel. +48 22 331 377 0
Fax +48 22 331 377 1

OOO Bystronic Laser
Berzarina Street, 12
123298 Moscow
Russia
Tel. +7 495 276 15 16
Fax +7 495 276 15 17

Bystronic Sales AG
Industriestrasse 21
CH-3362 Niederönz
Schweiz
Tel. +41 62 956 37 38
Fax +41 62 956 33 81

Bystronic PTE LTD
2 Leng Kee Road #03-05
Thye Hong Centre
Singapore 159086
Tel. +65 6472 6300
Fax +65 6472 6032


Bystronic Scandinavia AB
Metallvägen 30 A
SE-195 72 Rosersberg
Sverige
Tel. +46 8 594 415 50
Fax +46 8 594 415 55

269



Notizen

270



Notizen

271

